


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: FW26212424270015	TYPE: FW26212424270015	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.026*1	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 72.66 lm/W
MODEL	FW26212424270015	I _{max} (cd)	11158	S/MH (C0/180)	0.30	
NOMINAL POWER(W)	24	LOR (%)	100.0	S/MH (C90/270)	0.13	
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1786.8	□ UP,DN (C0-180)	0.6,67.9	
NOMINAL FLUX(lm)	1786.83	CIE CLASS	DIRECT	□ UP,DN (C180-360)	0.8,30.7	
LAMPS INSIDE	1	□ up (%)	1.4	CIBSE SHR NOM	0.00	
TEST VOLTAGE (V)	24	□ down (%)	98.6	CIBSE SHR MAX	0.30	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-11-16

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	258.3	504.0	846.6	793.2	276.6	158.1	133.6	168.9	0- 10	502.1	502.1	28.1,28.1
20	73.61	117.1	175.1	193.0	72.61	50.70	47.48	61.70	10- 20	556.6	1059	59.2,59.2
30	28.95	37.28	51.96	63.80	28.84	24.77	23.01	32.09	20- 30	275.2	1334	74.6,74.6
40	15.58	18.47	23.77	31.38	14.85	13.45	12.23	17.93	30- 40	160.9	1495	83.7,83.7
50	9.644	11.00	12.40	18.02	8.679	7.877	7.140	11.09	40- 50	109.4	1604	89.8,89.8
60	6.338	7.014	7.172	11.18	5.395	4.584	3.772	6.674	50- 60	76.24	1680	94,94
70	3.775	4.141	4.253	6.537	3.156	2.222	1.483	2.958	60- 70	50.03	1730	96.8,96.8
80	1.461	1.767	1.938	3.000	1.175	0.3859	0.0689	0.2812	70- 80	25.26	1756	98.3,98.3
90	0.0658	0.0985	0.2298	0.3427	0.0585	0.0274	0.0175	0.0444	80- 90	6.351	1762	98.6,98.6
100	0.0309	0.0310	0.0177	0.0434	0.0332	0.0420	0.0354	0.0695	90-100	0.5498	1763	98.6,98.6
110	0.0567	0.0530	0.0385	0.0750	0.0570	0.0662	0.0632	0.1089	100-110	0.5872	1763	98.7,98.7
120	0.0934	0.0850	0.0715	0.1181	0.0915	0.1021	0.1070	0.1714	110-120	0.8638	1764	98.7,98.7
130	0.1580	0.1387	0.1236	0.1922	0.1460	0.1681	0.1985	0.2898	120-130	1.238	1765	98.8,98.8
140	0.3028	0.2464	0.2278	0.3350	0.2662	0.3357	0.4507	0.6029	130-140	1.916	1767	98.9,98.9
150	0.6659	0.5291	0.4888	0.7055	0.5690	0.7616	1.146	1.402	140-150	3.299	1770	99.1,99.1
160	1.536	1.315	1.264	1.628	1.290	1.666	2.595	2.994	150-160	5.519	1776	99.4,99.4
170	3.156	2.921	2.949	3.466	2.727	2.998	4.198	4.968	160-170	7.031	1783	99.8,99.8
180	4.246	4.335	4.825	5.518	4.289	4.367	4.857	5.560	170-180	3.792	1787	100,100
DEG	LUMINOUS INTENSITY:X10cd									UNIT:lm		

Conical surface Flux(90deg): 1565.1 lm

%lum = 87.6%

%lamp = 87.6%

Conical surface Flux(120deg): 1680.4 lm

%lum = 94.0%


%lamp = 94.0%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-11-16

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

NAME: FW26212424270015	TYPE: FW26212424270015	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.026*1	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	3684	5028
80	3987	4267
75	5126	4741
70	5231	4755
65	5920	5341
60	6007	5485
55	6735	6570
50	7110	7375
45	8493	9755


C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2021-11-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity: 65.0%
 Test Distance: 5.749m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: FW26212424270015	TYPE: FW26212424270015	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.026*1	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-11-16

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: FW26212424270015	TYPE: FW26212424270015	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.026*1	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)					
0.0						
1.0	.179 .102 .032	.172 .098 .031	.159 .091 .029	.146 .084 .027	.135 .078 .025	
2.0	.168 .092 .028	.162 .089 .028	.151 .084 .026	.140 .079 .025	.131 .074 .023	
3.0	.157 .084 .025	.152 .081 .024	.142 .077 .023	.133 .073 .022	.125 .069 .021	
4.0	.147 .076 .022	.142 .074 .022	.134 .071 .021	.126 .068 .020	.119 .065 .020	
5.0	.137 .070 .020	.134 .069 .020	.126 .066 .019	.120 .063 .019	.113 .061 .018	
6.0	.129 .065 .019	.126 .064 .018	.119 .061 .018	.114 .059 .017	.108 .057 .017	
7.0	.122 .060 .017	.119 .059 .017	.113 .057 .016	.108 .055 .016	.103 .054 .016	
8.0	.115 .056 .016	.113 .055 .016	.108 .054 .015	.103 .052 .015	.099 .051 .015	
9.0	.109 .053 .015	.107 .052 .015	.102 .051 .014	.098 .049 .014	.094 .048 .014	
10.0	.104 .050 .014	.102 .049 .014	.098 .048 .013	.094 .047 .013	.090 .046 .013	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)					
0.0	.201 .201 .201	.172 .172 .172	.117 .117 .117	.067 .067 .067	.022 .022 .022	
1.0	.182 .168 .155	.156 .144 .134	.106 .099 .092	.061 .057 .054	.020 .018 .017	
2.0	.166 .143 .124	.143 .123 .107	.098 .085 .075	.056 .050 .044	.018 .016 .014	
3.0	.154 .124 .101	.132 .107 .088	.090 .075 .061	.052 .044 .036	.017 .014 .012	
4.0	.142 .110 .084	.122 .095 .073	.084 .066 .052	.049 .039 .031	.016 .013 .010	
5.0	.133 .098 .072	.114 .085 .063	.079 .059 .044	.046 .035 .026	.015 .011 .009	
6.0	.125 .088 .062	.107 .076 .054	.074 .054 .038	.043 .031 .023	.014 .010 .008	
7.0	.117 .080 .055	.101 .070 .048	.070 .049 .034	.040 .029 .020	.013 .009 .007	
8.0	.111 .074 .049	.095 .064 .042	.066 .045 .030	.038 .027 .018	.012 .009 .006	
9.0	.105 .069 .044	.091 .059 .038	.063 .042 .027	.037 .025 .016	.012 .008 .005	
10.0	.100 .064 .040	.086 .056 .035	.060 .039 .025	.035 .023 .015	.011 .008 .005	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-11-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: FW26212424270015					TYPE: FW26212424270015			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.: 0.026*1			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	14.1	14.9	14.3	15.1	15.3	13.9	14.8	14.1	14.9	15.1
	3H	15.3	16.1	15.5	16.3	16.5	14.9	15.7	15.1	15.9	16.1
	4H	15.7	16.5	16.0	16.7	17.0	15.3	16.0	15.6	16.3	16.5
	6H	16.1	16.8	16.4	17.0	17.3	15.6	16.3	15.9	16.6	16.9
	8H	16.1	16.8	16.5	17.1	17.4	15.7	16.4	16.1	16.7	17.0
	12H	16.1	16.8	16.5	17.1	17.4	15.8	16.5	16.2	16.8	17.1
4H	2H	14.5	15.3	14.8	15.5	15.8	14.4	15.2	14.7	15.4	15.6
	3H	16.0	16.6	16.3	16.9	17.2	15.6	16.2	15.9	16.5	16.8
	4H	16.6	17.2	17.0	17.5	17.9	16.1	16.7	16.4	17.0	17.3
	6H	17.0	17.6	17.4	17.9	18.3	16.5	17.1	16.9	17.4	17.8
	8H	17.2	17.7	17.6	18.0	18.4	16.7	17.2	17.1	17.6	18.0
	12H	17.2	17.7	17.6	18.1	18.5	16.8	17.3	17.2	17.7	18.1
8H	4H	16.8	17.3	17.2	17.7	18.1	16.3	16.8	16.7	17.2	17.6
	6H	17.4	17.8	17.8	18.2	18.7	16.9	17.3	17.3	17.7	18.2
	8H	17.6	17.9	18.0	18.4	18.8	17.1	17.5	17.6	18.0	18.4
	12H	17.7	18.0	18.2	18.5	19.0	17.3	17.6	17.8	18.1	18.6
12H	4H	16.8	17.3	17.2	17.6	18.1	16.3	16.8	16.8	17.2	17.6
	6H	17.4	17.8	17.9	18.2	18.7	16.9	17.3	17.4	17.8	18.2
	8H	17.6	17.9	18.1	18.4	18.9	17.2	17.5	17.7	18.0	18.5
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H		+ 0.3 / - 0.4					+ 0.3 / - 0.5				
1.5H		+ 0.2 / - 0.4					+ 0.4 / - 0.3				
2.0H		+ 0.3 / - 0.6					+ 0.6 / - 0.5				

CIE Pub.117, 1787 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 2.0)
Area: 0.026 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-11-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

NAME: FW26212424270015	TYPE: FW26212424270015	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.026*1	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	81	74	70	81	74	70	80	73	69	65
0.80	89	82	78	89	82	78	87	81	77	73
1.00	94	88	84	93	87	83	92	87	83	78
1.25	99	93	89	98	92	88	96	91	87	82
1.50	102	96	92	101	96	92	98	94	91	85
2.00	106	101	97	104	99	96	101	97	94	88
2.50	108	103	100	106	102	99	102	99	97	90
3.00	110	106	102	108	104	101	104	101	99	92
4.00	112	109	106	110	107	105	106	104	102	94
5.00	114	111	109	111	109	107	107	105	104	95
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2021-11-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: FW26212424270015	TYPE: FW26212424270015	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.026*1	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-11-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity:65.0%
 Test Distance:5.749m [K=1.0000]
 Remarks:

AAI Figure

NAME: FW26212424270015	TYPE: FW26212424270015	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.026*1	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-11-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

NAME: FW26212424270015	TYPE: FW26212424270015	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.026*1	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2021-11-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity: 65.0%
 Test Distance: 5.749m [K=1.0000]
 Remarks:

LED Avg.L Report

NAME: FW26212424270015	TYPE: FW26212424270015	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.026*1	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	4210
L_0~180 (75) av	3469
L_0~180 (85) av	2015
L_90~270 (65) av	3699
L_90~270 (75) av	2670
L_90~270 (85) av	2147
L_45 (65) av	5073
L_45 (75) av	3816
L_45 (85) av	2572

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2021-11-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2021-11-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: FW26212424270015	TYPE: FW26212424270015	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.026*1	Shielding Angle:

Table--1

UNIT: X10cd

C (DEG) □ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	694	694	694	694	694	694	694	694	694	694	694	694	694	694	694	694			
5	568	677	776	897	1001	1064	988	828	599	502	425	360	330	333	373	450			
10	258	372	504	684	847	945	793	564	277	199	158	138	134	142	169	222			
15	148	208	282	380	471	547	468	336	149	112	94.7	86.7	85.2	91.7	110	146			
20	73.6	95.2	117	154	175	203	193	163	72.6	57.9	50.7	47.4	47.5	51.9	61.7	82.1			
25	48.9	60.4	71.9	88.9	106	123	121	107	48.6	40.2	36.1	35.1	34.8	38.8	46.4	59.7			
30	28.9	33.3	37.3	44.2	52.0	61.4	63.8	61.1	28.8	26.4	24.8	22.8	23.0	25.6	32.1	41.1			
35	22.0	24.6	26.8	30.7	36.1	42.6	45.8	44.8	21.6	20.9	19.5	17.6	18.1	20.2	25.1	33.0			
40	15.6	17.2	18.5	20.4	23.8	28.3	31.4	30.6	14.8	14.9	13.5	12.4	12.2	14.2	17.9	24.2			
45	12.7	14.0	14.8	16.0	18.0	22.2	25.0	24.4	11.9	11.9	10.7	9.66	9.83	11.30	14.8	20.1			
50	9.64	10.6	11.0	11.3	12.4	15.5	18.0	17.9	8.68	8.78	7.88	7.09	7.14	8.40	11.09	15.6			
55	8.15	8.96	9.19	9.09	9.85	12.4	14.8	14.90	7.16	7.24	6.40	5.76	5.64	6.80	9.12	13.19			
60	6.34	7.02	7.01	6.68	7.17	9.02	11.18	11.44	5.40	5.40	4.58	4.01	3.77	4.67	6.67	10.01			
65	5.28	5.90	5.76	5.48	5.90	7.35	9.16	9.56	4.45	4.36	3.60	2.95	2.74	3.37	5.18	8.06			
70	3.78	4.36	4.14	4.00	4.25	5.36	6.54	7.11	3.16	2.83	2.22	1.65	1.48	1.82	2.96	5.23			
75	2.80	3.35	3.15	2.98	3.21	4.06	5.08	5.53	2.31	1.88	1.38	0.94	0.77	0.94	1.74	3.38			
80	1.46	1.81	1.77	1.75	1.94	2.48	3.00	3.05	1.18	0.75	0.39	0.13	0.07	0.07	0.28	1.20			
85	0.68	0.94	0.96	0.99	1.15	1.52	1.77	1.65	0.53	0.24	0.05	0.02	0.01	0.02	0.04	0.24			
90	0.07	0.08	0.10	0.15	0.23	0.33	0.34	0.25	0.06	0.05	0.03	0.02	0.02	0.03	0.04	0.09			
95	0.06	0.05	0.03	0.02	0.03	0.04	0.04	0.08	0.05	0.05	0.03	0.02	0.02	0.03	0.05	0.10			
100	0.03	0.06	0.03	0.02	0.02	0.03	0.04	0.08	0.03	0.06	0.04	0.03	0.04	0.05	0.07	0.11			
105	0.04	0.06	0.04	0.03	0.02	0.03	0.05	0.09	0.04	0.07	0.05	0.04	0.05	0.06	0.08	0.12			
110	0.06	0.08	0.05	0.04	0.04	0.05	0.08	0.12	0.06	0.08	0.07	0.06	0.06	0.08	0.11	0.14			
115	0.07	0.09	0.06	0.05	0.05	0.06	0.09	0.14	0.07	0.09	0.08	0.07	0.08	0.10	0.13	0.16			
120	0.09	0.10	0.09	0.07	0.07	0.09	0.12	0.17	0.09	0.11	0.10	0.10	0.11	0.14	0.17	0.20			
125	0.11	0.12	0.10	0.09	0.09	0.11	0.15	0.20	0.11	0.12	0.12	0.12	0.14	0.17	0.21	0.22			
130	0.16	0.16	0.14	0.12	0.12	0.15	0.19	0.26	0.15	0.15	0.17	0.18	0.20	0.25	0.29	0.29			
135	0.20	0.19	0.17	0.16	0.16	0.18	0.24	0.32	0.18	0.20	0.22	0.24	0.27	0.33	0.38	0.39			
140	0.30	0.28	0.25	0.23	0.23	0.27	0.33	0.46	0.27	0.30	0.34	0.39	0.45	0.55	0.60	0.59			
145	0.41	0.37	0.32	0.30	0.30	0.35	0.44	0.60	0.36	0.41	0.46	0.55	0.66	0.81	0.85	0.81			
150	0.67	0.60	0.53	0.49	0.49	0.57	0.71	0.95	0.57	0.65	0.76	0.95	1.15	1.38	1.40	1.28			
155	0.93	0.85	0.76	0.71	0.72	0.82	0.99	1.30	0.79	0.89	1.05	1.33	1.61	1.91	1.93	1.74			
160	1.54	1.43	1.32	1.26	1.26	1.40	1.63	2.08	1.29	1.41	1.67	2.11	2.59	3.03	2.99	2.68			
165	2.10	1.99	1.85	1.79	1.80	1.97	2.24	2.77	1.77	1.89	2.16	2.73	3.41	3.91	3.84	3.46			
170	3.16	3.07	2.92	2.90	2.95	3.18	3.47	4.02	2.73	2.83	3.00	3.45	4.20	4.77	4.97	4.74			
175	3.84	3.79	3.69	3.78	3.89	4.15	4.36	4.93	3.47	3.57	3.69	3.95	4.38	4.90	5.42	5.55			
180	4.25	4.32	4.34	4.60	4.83	5.12	5.52	6.17	4.29	4.28	4.37	4.57	4.86	5.09	5.56	6.12			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-11-16

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks: