


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: 2835 IP20	TYPE: 2835 2400LED 12V	WEIGHT:
SPEC.: 202-00312-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 129.63 lm/W			
MODEL	4000K	I _{max} (cd)	276.9	S/MH(C0/180)	1.28
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.29
RATED VOLTAGE(V)	12	TOTAL FLUX(lm)	823.75	□ UP,DN(C0-180)	0.7,48.7
NOMINAL FLUX(lm)	3.43229	CIE CLASS	DIRECT	□ UP,DN(C180-360)	0.6,50.0
LAMPS INSIDE	240	□ up (%)	1.3	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	12	□ down (%)	98.7	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2022-03-23

□ Range: 0 - 180DEG
 □ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity:65.0%
 Test Distance:5.749m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	272.2	271.3	271.2	271.9	272.8	273.7	273.7	273.1	0- 10	26.22	26.22	3.18,3.18
20	259.0	257.3	257.1	258.3	260.1	261.7	261.8	260.7	10- 20	75.40	101.6	12.3,12.3
30	237.5	235.1	234.8	236.6	239.0	241.2	241.3	239.8	20- 30	115.2	216.8	26.3,26.3
40	207.9	205.2	205.0	207.1	209.8	212.4	212.5	210.6	30- 40	140.4	357.2	43.4,43.4
50	170.7	168.0	168.1	170.4	173.0	175.8	175.7	173.5	40- 50	147.5	504.7	61.3,61.3
60	126.7	124.4	124.8	127.2	129.5	132.1	131.8	129.5	50- 60	134.7	639.4	77.6,77.6
70	77.46	75.84	76.58	78.96	80.42	82.59	81.99	79.67	60- 70	103.0	742.3	90.1,90.1
80	17.26	27.88	28.87	30.74	31.36	32.58	31.85	30.06	70- 80	57.13	799.5	97.1,97.1
90	0.2739	1.334	1.820	2.044	0.2433	1.656	1.282	1.314	80- 90	13.38	812.9	98.7,98.7
100	0.6883	0.7208	0.8003	0.6930	0.5606	0.5479	0.5601	0.5775	90-100	0.7375	813.6	98.8,98.8
110	1.286	1.266	1.259	1.232	1.073	0.9979	1.010	1.033	100-110	0.9288	814.5	98.9,98.9
120	1.870	1.804	1.797	1.776	1.605	1.472	1.494	1.508	110-120	1.385	815.9	99,99
130	2.388	2.287	2.262	2.262	2.088	1.919	1.927	1.948	120-130	1.697	817.6	99.3,99.3
140	2.793	2.680	2.648	2.671	2.479	2.321	2.270	2.327	130-140	1.801	819.4	99.5,99.5
150	3.103	3.013	2.946	3.006	2.794	2.662	2.584	2.676	140-150	1.685	821.1	99.7,99.7
160	3.341	3.285	3.284	3.265	3.089	2.978	2.963	3.014	150-160	1.384	822.5	99.8,99.8
170	3.582	3.556	3.586	3.523	3.423	3.347	3.358	3.389	160-170	0.9319	823.4	100,100
180	3.797	3.770	3.829	3.804	3.797	3.770	3.827	3.802	170-180	0.3426	823.8	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 446.09 lm

%lum = 54.2%

%lamp = 54.2%

Conical surface Flux(120deg): 639.39 lm

%lum = 77.6%


%lamp = 77.6%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-23

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

NAME: 2835 IP20	TYPE: 2835 2400LED 12V	WEIGHT:
SPEC.: 202-00312-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	339	15593
80	9915	16602
75	22115	22011
70	22595	22358
65	25379	25051
60	25287	24921
55	26763	26363
50	26502	26107
45	27357	26977


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-23

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: 2835 IP20	TYPE: 2835 2400LED 12V	WEIGHT:
SPEC.: 202-00312-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.04	.99	.95	1.01	.97	.94	.97	.94	.91	.93	.90	.88	.89	.87	.85	.83
2.0	.90	.83	.78	.88	.82	.76	.84	.79	.74	.81	.76	.73	.78	.74	.71	.69
3.0	.79	.71	.64	.77	.70	.64	.74	.68	.62	.71	.66	.61	.68	.64	.60	.58
4.0	.70	.61	.54	.68	.60	.54	.66	.59	.53	.63	.57	.52	.61	.56	.51	.49
5.0	.62	.53	.47	.61	.53	.46	.59	.51	.46	.57	.50	.45	.55	.49	.44	.42
6.0	.56	.47	.41	.55	.46	.40	.53	.45	.40	.51	.44	.39	.50	.44	.39	.37
7.0	.51	.42	.36	.50	.41	.36	.48	.41	.35	.47	.40	.35	.45	.39	.34	.32
8.0	.46	.38	.32	.45	.37	.32	.44	.37	.31	.43	.36	.31	.41	.35	.31	.29
9.0	.42	.34	.29	.42	.34	.28	.40	.33	.28	.39	.33	.28	.38	.32	.28	.26
10.0	.39	.31	.26	.39	.31	.26	.37	.30	.26	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-23

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: 2835 IP20	TYPE: 2835 2400LED 12V	WEIGHT:
SPEC.: 202-00312-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Wall Exitance Coefficients(WEC)
0.0						
1.0	.308 .175 .056	.301 .172 .055	.287 .165 .053	.274 .158 .051	.262 .152 .049	
2.0	.292 .160 .049	.285 .157 .048	.273 .152 .047	.261 .146 .046	.251 .142 .045	
3.0	.270 .144 .043	.264 .142 .043	.253 .137 .042	.243 .133 .041	.234 .129 .040	
4.0	.250 .130 .038	.244 .128 .038	.235 .124 .037	.226 .121 .037	.217 .118 .036	
5.0	.231 .118 .034	.226 .116 .034	.217 .113 .033	.209 .110 .033	.202 .108 .032	
6.0	.214 .107 .031	.210 .106 .031	.202 .104 .030	.195 .101 .030	.188 .099 .029	
7.0	.199 .098 .028	.196 .097 .028	.189 .095 .027	.182 .093 .027	.176 .091 .027	
8.0	.186 .091 .026	.183 .090 .025	.176 .088 .025	.171 .086 .025	.165 .085 .025	
9.0	.174 .084 .024	.171 .084 .023	.166 .082 .023	.160 .080 .023	.155 .079 .023	
10.0	.164 .079 .022	.161 .078 .022	.156 .076 .022	.151 .075 .021	.147 .074 .021	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Ceiling Cavity Exitance Coefficients(CCEC)
0.0	.201 .201 .201	.171 .171 .171	.117 .117 .117	.067 .067 .067	.021 .021 .021	
1.0	.190 .166 .145	.163 .143 .124	.111 .098 .086	.064 .057 .050	.021 .018 .016	
2.0	.182 .142 .108	.156 .122 .094	.107 .085 .065	.062 .049 .038	.020 .016 .012	
3.0	.175 .125 .085	.150 .107 .073	.103 .075 .051	.059 .044 .030	.019 .014 .010	
4.0	.167 .111 .069	.144 .096 .060	.099 .067 .042	.057 .039 .025	.018 .013 .008	
5.0	.160 .101 .057	.137 .087 .050	.095 .061 .035	.055 .036 .021	.018 .012 .007	
6.0	.153 .093 .049	.131 .080 .043	.091 .056 .030	.053 .033 .018	.017 .011 .006	
7.0	.146 .086 .044	.126 .074 .038	.087 .052 .027	.050 .031 .016	.016 .010 .005	
8.0	.140 .080 .039	.120 .069 .034	.083 .049 .024	.048 .029 .014	.016 .009 .005	
9.0	.133 .075 .036	.115 .065 .031	.080 .046 .022	.046 .027 .013	.015 .009 .004	
10.0	.128 .071 .033	.110 .061 .029	.076 .043 .020	.045 .026 .012	.014 .008 .004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-23

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: 2835 IP20					TYPE: 2835 2400LED 12V			WEIGHT:			
SPEC.: 202-00312-00					DIM.:			SERIAL No.:			
MFR.:					SUR.: 0.01*0.5			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	24.8	26.3	25.1	26.5	26.8	24.7	26.2	25.0	26.5	26.7
	3H	26.3	27.7	26.6	27.9	28.2	26.2	27.6	26.5	27.9	28.1
	4H	26.8	28.2	27.2	28.4	28.7	26.8	28.1	27.1	28.4	28.7
	6H	27.1	28.3	27.4	28.6	28.9	27.1	28.4	27.5	28.7	29.0
	8H	27.1	28.3	27.4	28.6	28.9	27.2	28.4	27.6	28.7	29.0
	12H	27.0	28.2	27.4	28.5	28.8	27.2	28.4	27.6	28.7	29.0
4H	2H	25.4	26.7	25.7	27.0	27.3	25.3	26.7	25.7	26.9	27.2
	3H	27.0	28.2	27.4	28.5	28.8	27.0	28.2	27.4	28.5	28.8
	4H	27.7	28.8	28.1	29.1	29.5	27.7	28.7	28.1	29.1	29.4
	6H	28.1	29.0	28.5	29.4	29.8	28.1	29.1	28.5	29.4	29.8
	8H	28.1	28.9	28.5	29.3	29.7	28.2	29.1	28.7	29.5	29.9
	12H	28.0	28.8	28.5	29.2	29.7	28.3	29.1	28.7	29.5	29.9
8H	4H	27.9	28.8	28.4	29.2	29.6	27.9	28.8	28.3	29.2	29.6
	6H	28.4	29.1	28.9	29.6	30.0	28.5	29.2	28.9	29.6	30.1
	8H	28.5	29.1	29.0	29.6	30.0	28.6	29.3	29.1	29.7	30.2
	12H	28.5	29.0	29.0	29.5	30.0	28.7	29.3	29.2	29.8	30.3
12H	4H	27.9	28.7	28.4	29.1	29.6	27.9	28.7	28.3	29.1	29.5
	6H	28.4	29.1	28.9	29.5	30.0	28.5	29.1	29.0	29.6	30.1
	8H	28.5	29.1	29.0	29.6	30.1	28.7	29.2	29.2	29.7	30.2
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H		+ 0.1 / - 0.2					+ 0.2 / - 0.2				
1.5H		+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H		+ 0.2 / - 0.3					+ 0.2 / - 0.3				

CIE Pub.117, 823.8 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.7)
Area: 0.01 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-23

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:


```

Range: 0 - 180DEG
Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

```

ISOCANDELA DIAGRAM

NAME: 2835 IP20	TYPE: 2835 2400LED 12V	WEIGHT:
SPEC.: 202-00312-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-23

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

AAI Figure

NAME: 2835 IP20	TYPE: 2835 2400LED 12V	WEIGHT:
SPEC.: 202-00312-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2022-03-23

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity:65.0%
 Test Distance:5.749m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

NAME: 2835 IP20	TYPE: 2835 2400LED 12V	WEIGHT:
SPEC.: 202-00312-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-23

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

LED Avg.L Report

NAME: 2835 IP20	TYPE: 2835 2400LED 12V	WEIGHT:
SPEC.: 202-00312-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	24612
L_0~180 (75) av	20806
L_0~180 (85) av	6665
L_90~270 (65) av	24685
L_90~270 (75) av	20951
L_90~270 (85) av	12922
L_45 (65) av	24676
L_45 (75) av	20904
L_45 (85) av	13059

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-23

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-23

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 2835 IP20	TYPE: 2835 2400LED 12V	WEIGHT:
SPEC.: 202-00312-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:

Table--1

UNIT: cd

C (DEG) □ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	277	277	277	277	277	277	277	277	277	277	277	277	277	277	277	277			
5	276	276	276	276	276	276	276	276	276	276	277	277	277	277	276	276			
10	272	272	271	271	271	272	272	272	273	273	274	274	274	273	273	273			
15	268	267	267	267	267	267	267	268	269	269	270	270	270	270	269	269			
20	259	258	257	257	257	258	258	259	260	261	262	262	262	261	261	260			
25	251	250	249	249	249	250	251	252	253	253	254	255	255	254	253	252			
30	237	236	235	235	235	236	237	238	239	240	241	241	241	240	240	239			
35	227	225	224	224	224	225	226	227	228	229	231	231	231	230	229	228			
40	208	207	205	205	205	206	207	209	210	211	212	212	212	211	211	209			
45	194	193	191	191	191	192	193	195	196	197	199	199	199	197	197	195			
50	171	170	168	168	168	170	170	172	173	174	176	176	176	174	174	172			
55	154	153	151	152	151	153	154	156	156	158	159	159	159	157	157	155			
60	127	126	124	125	125	127	127	129	129	130	132	132	132	130	129	128			
65	108	107	105	106	106	108	108	110	110	111	113	112	112	111	110	108			
70	77.5	77.0	75.8	76.6	76.6	78.5	79.0	80.3	80.4	81.1	82.6	82.0	82.0	80.3	79.7	77.9			
75	57.4	56.8	56.0	56.7	57.1	58.7	59.2	60.1	60.2	60.8	62.1	61.5	61.4	59.8	59.2	57.6			
80	17.3	28.5	27.9	28.6	28.9	30.3	30.7	31.5	31.4	31.7	32.6	32.0	31.9	30.5	30.1	28.9			
85	0.30	13.3	12.8	13.3	13.6	14.8	15.1	15.6	15.4	15.6	16.1	15.6	15.4	14.5	14.2	13.5			
90	0.27	1.02	1.33	1.64	1.82	2.06	2.04	1.75	0.24	1.20	1.66	1.43	1.28	1.22	1.31	0.95			
95	0.41	0.45	0.69	0.83	0.89	0.87	0.73	0.51	0.33	0.40	0.53	0.53	0.51	0.53	0.49	0.36			
100	0.69	0.70	0.72	0.76	0.80	0.76	0.69	0.67	0.56	0.55	0.55	0.56	0.56	0.58	0.58	0.58			
105	0.92	0.91	0.93	0.93	0.93	0.91	0.90	0.87	0.75	0.72	0.72	0.73	0.73	0.74	0.75	0.75			
110	1.29	1.25	1.27	1.26	1.26	1.25	1.23	1.21	1.07	1.00	1.00	1.01	1.01	1.02	1.03	1.04			
115	1.52	1.47	1.49	1.48	1.49	1.47	1.46	1.44	1.29	1.20	1.19	1.19	1.20	1.22	1.23	1.23			
120	1.87	1.80	1.80	1.80	1.80	1.79	1.78	1.77	1.60	1.50	1.47	1.47	1.49	1.50	1.51	1.53			
125	2.08	2.01	2.01	2.00	1.99	1.99	1.98	1.97	1.81	1.70	1.66	1.66	1.67	1.68	1.69	1.72			
130	2.39	2.30	2.29	2.27	2.26	2.27	2.26	2.27	2.09	1.98	1.92	1.92	1.93	1.94	1.95	2.00			
135	2.56	2.48	2.46	2.44	2.43	2.44	2.44	2.45	2.26	2.15	2.09	2.08	2.07	2.09	2.10	2.18			
140	2.79	2.73	2.68	2.66	2.65	2.68	2.67	2.69	2.48	2.38	2.32	2.30	2.27	2.30	2.33	2.42			
145	2.93	2.87	2.82	2.79	2.77	2.82	2.82	2.83	2.61	2.52	2.47	2.44	2.39	2.43	2.47	2.56			
150	3.10	3.06	3.01	2.96	2.95	3.01	3.01	3.01	2.79	2.71	2.66	2.64	2.58	2.62	2.68	2.77			
155	3.20	3.17	3.13	3.07	3.08	3.13	3.12	3.12	2.91	2.83	2.78	2.77	2.73	2.75	2.81	2.90			
160	3.34	3.32	3.28	3.23	3.28	3.29	3.26	3.27	3.09	3.02	2.98	2.97	2.96	2.95	3.01	3.11			
165	3.43	3.42	3.39	3.34	3.42	3.39	3.36	3.37	3.21	3.16	3.11	3.11	3.13	3.10	3.16	3.24			
170	3.58	3.58	3.56	3.52	3.59	3.55	3.52	3.54	3.42	3.38	3.35	3.34	3.36	3.34	3.39	3.46			
175	3.68	3.67	3.67	3.65	3.70	3.66	3.64	3.66	3.58	3.54	3.52	3.52	3.55	3.53	3.56	3.62			
180	3.80	3.78	3.77	3.77	3.83	3.80	3.80	3.82	3.80	3.78	3.77	3.78	3.83	3.80	3.80	3.83			

C Range: 0 - 360DEG

C Interval: 22.5DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:

Test Date:2022-03-23

□ Range: 0 - 180DEG

□ Interval: 2.0DEG

Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450

Humidity:65.0%

Test Distance:5.749m [K=1.0000]

Remarks: