


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 114.90 lm/W
MODEL	6500K	I _{max} (cd)	282.1	S/MH(C0/180)	1.29	
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.25	
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	850.90	□ UP,DN(C0-180)	0.7,52.2	
NOMINAL FLUX(lm)	6.07788	CIE CLASS	DIRECT	□ UP,DN(C180-360)	0.6,46.4	
LAMPS INSIDE	140	□ up (%)	1.4	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	24	□ down (%)	98.6	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2022-03-22

□ Range: 0 - 180DEG
 □ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity:65.0%
 Test Distance:5.749m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	277.3	279.4	280.2	279.7	277.9	275.9	274.9	275.5	0- 10	26.70	26.70	3.14,3.14
20	264.4	268.5	270.2	269.1	265.4	261.4	259.4	260.6	10- 20	76.89	103.6	12.2,12.2
30	243.1	249.2	251.8	250.1	244.6	238.5	235.6	237.5	20- 30	117.7	221.3	26,26
40	213.5	221.5	225.0	222.8	215.4	207.4	203.7	206.1	30- 40	144.0	365.3	42.9,42.9
50	176.0	185.9	190.1	187.4	178.4	168.4	164.0	166.9	40- 50	151.7	517.0	60.8,60.8
60	131.1	142.9	147.9	144.8	133.8	122.4	117.3	120.6	50- 60	139.0	656.0	77.1,77.1
70	80.58	93.66	99.45	95.73	83.40	71.18	66.07	69.45	60- 70	106.7	762.8	89.6,89.6
80	30.48	42.66	48.47	44.63	32.76	22.68	19.09	21.45	70- 80	60.18	822.9	96.7,96.7
90	0.3242	4.883	7.792	6.011	0.3101	0.6275	0.5154	0.6096	80- 90	16.39	839.3	98.6,98.6
100	0.7458	0.6350	0.6291	0.6337	0.6110	0.7192	0.7773	0.7343	90-100	1.065	840.4	98.8,98.8
110	1.337	1.146	1.092	1.135	1.126	1.207	1.269	1.221	100-110	0.9765	841.4	98.9,98.9
120	1.926	1.694	1.643	1.693	1.672	1.700	1.758	1.717	110-120	1.438	842.8	99,99
130	2.434	2.189	2.140	2.203	2.166	2.157	2.179	2.157	120-130	1.756	844.6	99.3,99.3
140	2.837	2.622	2.553	2.652	2.571	2.549	2.523	2.532	130-140	1.860	846.4	99.5,99.5
150	3.150	2.989	2.926	3.016	2.898	2.878	2.816	2.871	140-150	1.741	848.2	99.7,99.7
160	3.395	3.293	3.309	3.305	3.198	3.180	3.167	3.178	150-160	1.430	849.6	99.8,99.8
170	3.648	3.607	3.656	3.605	3.539	3.523	3.547	3.529	160-170	0.9620	850.6	100,100
180	3.899	3.891	3.941	3.914	3.896	3.891	3.941	3.911	170-180	0.3532	850.9	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 456.68 lm

%lum = 53.7%

%lamp = 53.7%

Conical surface Flux(120deg): 656.03 lm

%lum = 77.1%


%lamp = 77.1%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	20609	42541
80	21879	34928
75	28884	38210
70	29370	36382
65	32859	38240
60	32692	37012
55	34524	37966
50	34122	37016
45	35161	37514


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

<input type="checkbox"/> cc	80%			70%			50%			30%			10%			0
<input type="checkbox"/> w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
<input type="checkbox"/> fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.90	.87	.89	.86	.84	.82
2.0	.90	.83	.77	.88	.82	.76	.84	.79	.74	.81	.76	.72	.77	.74	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.61	.68	.63	.59	.57
4.0	.70	.61	.54	.68	.60	.53	.65	.58	.53	.63	.57	.52	.61	.55	.51	.49
5.0	.62	.53	.46	.61	.52	.46	.59	.51	.45	.56	.50	.45	.54	.49	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.40	.51	.44	.39	.49	.43	.39	.36
7.0	.50	.42	.35	.50	.41	.35	.48	.40	.35	.46	.40	.35	.45	.39	.34	.32
8.0	.46	.37	.32	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.31	.29
9.0	.42	.34	.28	.42	.34	.28	.40	.33	.28	.39	.32	.28	.38	.32	.28	.26
10.0	.39	.31	.26	.38	.31	.26	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)					
0.0						
1.0	.313 .178 .056	.305 .174 .055	.291 .167 .053	.278 .160 .051	.266 .154 .050	
2.0	.294 .161 .049	.287 .158 .049	.275 .153 .047	.263 .148 .046	.253 .143 .045	
3.0	.272 .145 .043	.266 .142 .043	.255 .138 .042	.245 .134 .041	.235 .130 .040	
4.0	.251 .130 .038	.246 .129 .038	.236 .125 .037	.227 .122 .037	.218 .119 .036	
5.0	.232 .118 .034	.227 .117 .034	.218 .114 .033	.210 .111 .033	.203 .108 .033	
6.0	.215 .108 .031	.211 .106 .031	.203 .104 .030	.196 .102 .030	.189 .099 .030	
7.0	.200 .099 .028	.196 .098 .028	.189 .096 .028	.183 .094 .027	.176 .092 .027	
8.0	.187 .091 .026	.183 .090 .025	.177 .088 .025	.171 .087 .025	.165 .085 .025	
9.0	.175 .085 .024	.172 .084 .023	.166 .082 .023	.161 .081 .023	.156 .079 .023	
10.0	.164 .079 .022	.162 .078 .022	.156 .077 .022	.152 .075 .021	.147 .074 .021	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)					
0.0	.201 .201 .201	.172 .172 .172	.117 .117 .117	.067 .067 .067	.022 .022 .022	
1.0	.191 .167 .145	.163 .143 .124	.112 .098 .086	.064 .057 .050	.021 .018 .016	
2.0	.183 .142 .108	.157 .123 .094	.107 .085 .065	.062 .049 .038	.020 .016 .012	
3.0	.175 .125 .085	.150 .108 .073	.103 .075 .051	.060 .044 .030	.019 .014 .010	
4.0	.168 .112 .069	.144 .096 .060	.099 .067 .042	.057 .039 .025	.018 .013 .008	
5.0	.160 .101 .058	.138 .088 .050	.095 .061 .035	.055 .036 .021	.018 .012 .007	
6.0	.153 .093 .050	.132 .081 .043	.091 .056 .031	.053 .033 .018	.017 .011 .006	
7.0	.147 .086 .044	.126 .075 .038	.087 .052 .027	.051 .031 .016	.016 .010 .005	
8.0	.140 .080 .039	.121 .070 .034	.083 .049 .024	.049 .029 .014	.016 .009 .005	
9.0	.134 .075 .036	.115 .065 .031	.080 .046 .022	.047 .027 .013	.015 .009 .004	
10.0	.128 .071 .033	.111 .062 .029	.077 .043 .021	.045 .026 .012	.015 .008 .004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: 2835 IP20					TYPE: 2835 140LED 24V			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.: 0.008*0.5			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.8	27.4	26.1	27.6	27.8	26.3	27.8	26.6	28.0	28.3	
	3H	27.4	28.8	27.7	29.0	29.3	28.0	29.4	28.4	29.7	
	4H	27.9	29.3	28.3	29.5	29.8	28.8	30.1	29.1	30.4	
	6H	28.3	29.5	28.6	29.8	30.1	29.4	30.7	29.8	31.0	
	8H	28.4	29.6	28.7	29.9	30.2	29.6	30.8	30.0	31.1	
	12H	28.4	29.6	28.8	29.9	30.2	29.8	31.0	30.2	31.3	
4H	2H	26.6	27.9	26.9	28.2	28.5	26.9	28.2	27.2	28.5	
	3H	28.3	29.5	28.7	29.8	30.1	28.9	30.0	29.2	30.3	
	4H	29.0	30.1	29.4	30.4	30.8	29.8	30.8	30.2	31.2	
	6H	29.5	30.4	29.9	30.8	31.2	30.5	31.4	30.9	31.8	
	8H	29.6	30.5	30.0	30.9	31.3	30.8	31.7	31.2	32.1	
	12H	29.7	30.5	30.1	30.9	31.3	31.0	31.8	31.5	32.2	
8H	4H	29.4	30.2	29.8	30.6	31.0	30.0	30.9	30.5	31.3	
	6H	30.0	30.7	30.5	31.2	31.6	30.9	31.7	31.4	32.1	
	8H	30.2	30.9	30.7	31.3	31.8	31.3	32.0	31.8	32.4	
	12H	30.4	30.9	30.9	31.4	31.9	31.7	32.3	32.2	32.7	
12H	4H	29.4	30.2	29.8	30.6	31.1	30.0	30.8	30.5	31.3	
	6H	30.1	30.8	30.6	31.2	31.7	31.0	31.7	31.5	32.1	
	8H	30.4	30.9	30.9	31.4	31.9	31.5	32.0	32.0	32.5	
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.4					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.1 / - 0.3					

CIE Pub.117, 850.9 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.6)
Area: 0.008 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:


```

Range: 0 - 180DEG
Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

```

ISOCANDELA DIAGRAM

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

AAI Figure

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

LED Avg.L Report

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	31877
L_0~180 (75) av	27100
L_0~180 (85) av	16658
L_90~270 (65) av	31989
L_90~270 (75) av	27738
L_90~270 (85) av	21300
L_45 (65) av	31967
L_45 (75) av	27481
L_45 (85) av	19514

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity: 65.0%
 Test Distance: 5.749m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

Table--1

UNIT: cd

C (DEG) □ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	282	282	282	282	282	282	282	282	282	282	282	282	282	282	282	282			
5	281	281	282	282	282	282	282	282	281	281	280	280	280	280	280	281			
10	277	279	279	280	280	280	280	279	278	277	276	275	275	275	275	276			
15	273	275	276	277	277	277	276	275	274	272	271	270	270	270	271	272			
20	264	267	268	270	270	270	269	268	265	263	261	260	259	260	261	262			
25	257	260	262	263	264	264	263	261	258	255	253	251	251	251	252	254			
30	243	247	249	251	252	252	250	248	245	241	238	236	236	236	237	240			
35	232	236	239	241	242	242	240	238	234	230	227	225	224	224	226	229			
40	213	218	222	224	225	225	223	220	215	211	207	204	204	204	206	209			
45	199	205	208	211	212	212	210	206	202	196	193	189	189	189	191	195			
50	176	182	186	189	190	190	187	184	178	173	168	165	164	164	167	171			
55	159	165	170	173	174	174	171	167	161	155	151	147	146	146	149	153			
60	131	138	143	147	148	148	145	140	134	127	122	118	117	118	121	125			
65	111	119	124	128	129	129	126	121	114	107	102	98.0	97.1	97.3	101	105			
70	80.6	88.3	93.7	98.5	99.4	99.4	95.7	90.8	83.4	75.2	71.2	67.1	66.1	66.4	69.5	73.7			
75	60.0	67.5	73.1	78.0	79.0	78.9	75.2	70.0	62.5	54.5	50.6	46.7	45.8	46.1	49.0	53.1			
80	30.5	37.4	42.7	47.4	48.5	48.2	44.6	39.6	32.8	25.3	22.7	19.7	19.1	19.3	21.4	24.7			
85	14.4	19.9	24.4	28.6	29.6	29.4	26.2	21.9	16.0	11.5	8.98	7.05	6.55	6.65	8.02	10.3			
90	0.32	2.70	4.88	7.16	7.79	7.77	6.01	3.73	0.31	0.79	0.63	0.52	0.52	0.55	0.61	0.70			
95	0.45	0.45	0.73	1.19	1.33	1.28	0.86	0.64	0.38	0.44	0.51	0.56	0.56	0.57	0.53	0.45			
100	0.75	0.66	0.63	0.63	0.63	0.63	0.63	0.66	0.61	0.66	0.72	0.76	0.78	0.76	0.73	0.69			
105	0.97	0.86	0.82	0.79	0.79	0.79	0.81	0.86	0.80	0.84	0.90	0.95	0.97	0.95	0.92	0.87			
110	1.34	1.20	1.15	1.10	1.09	1.10	1.13	1.19	1.13	1.15	1.21	1.25	1.27	1.25	1.22	1.17			
115	1.58	1.42	1.37	1.33	1.32	1.33	1.36	1.42	1.35	1.36	1.40	1.45	1.47	1.46	1.42	1.37			
120	1.93	1.76	1.69	1.65	1.64	1.65	1.69	1.75	1.67	1.67	1.70	1.74	1.76	1.75	1.72	1.68			
125	2.14	1.97	1.90	1.86	1.85	1.86	1.90	1.97	1.88	1.87	1.89	1.92	1.94	1.93	1.90	1.88			
130	2.43	2.28	2.19	2.14	2.14	2.16	2.20	2.28	2.17	2.16	2.16	2.17	2.18	2.18	2.16	2.16			
135	2.61	2.47	2.36	2.32	2.31	2.35	2.39	2.47	2.34	2.33	2.33	2.32	2.33	2.33	2.31	2.34			
140	2.84	2.72	2.62	2.56	2.55	2.61	2.65	2.72	2.57	2.56	2.55	2.55	2.52	2.53	2.53	2.57			
145	2.97	2.87	2.77	2.70	2.71	2.77	2.81	2.86	2.71	2.70	2.69	2.68	2.64	2.66	2.67	2.72			
150	3.15	3.07	2.99	2.92	2.93	3.00	3.02	3.05	2.90	2.88	2.88	2.88	2.82	2.84	2.87	2.91			
155	3.25	3.19	3.12	3.06	3.09	3.14	3.14	3.18	3.02	3.00	3.00	3.01	2.95	2.96	2.99	3.03			
160	3.40	3.35	3.29	3.25	3.31	3.32	3.31	3.34	3.20	3.19	3.18	3.19	3.17	3.15	3.18	3.22			
165	3.50	3.46	3.42	3.37	3.47	3.44	3.42	3.45	3.33	3.32	3.30	3.31	3.31	3.27	3.30	3.35			
170	3.65	3.63	3.61	3.58	3.66	3.62	3.60	3.63	3.54	3.53	3.52	3.53	3.55	3.50	3.53	3.57			
175	3.76	3.75	3.74	3.73	3.79	3.75	3.74	3.76	3.69	3.68	3.68	3.69	3.71	3.67	3.69	3.73			
180	3.90	3.89	3.89	3.90	3.94	3.91	3.91	3.93	3.90	3.89	3.89	3.91	3.94	3.91	3.91	3.93			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks: