


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 107.66 lm/W
MODEL	3000K	I _{max} (cd)	270.7	S/MH(C0/180)	1.28	
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.26	
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	800.66	<input type="checkbox"/> UP,DN(C0-180)	0.7,50.7	
NOMINAL FLUX(lm)	5.71897	CIE CLASS	DIRECT	<input type="checkbox"/> UP,DN(C180-360)	0.7,47.9	
LAMPS INSIDE	140	<input type="checkbox"/> up (%)	1.4	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	24	<input type="checkbox"/> down (%)	98.6	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	266.2	266.9	267.2	267.1	266.4	265.6	265.3	265.5	0- 10	25.62	25.62	3.2,3.2
20	253.3	254.7	255.2	254.8	253.4	252.0	251.2	251.7	10- 20	73.64	99.26	12.4,12.4
30	232.0	234.2	235.0	234.4	232.2	230.1	228.9	229.6	20- 30	112.3	211.6	26.4,26.4
40	202.9	205.9	207.0	206.2	203.3	200.4	198.8	199.6	30- 40	136.7	348.3	43.5,43.5
50	166.5	170.4	171.9	170.9	167.2	163.5	161.4	162.5	40- 50	143.2	491.5	61.4,61.4
60	123.7	128.5	130.4	129.1	124.5	118.4	117.6	118.8	50- 60	130.5	621.9	77.7,77.7
70	75.87	81.51	83.74	82.26	76.80	71.37	69.13	70.30	60- 70	99.16	721.1	90.1,90.1
80	28.31	33.76	36.18	34.59	28.40	24.83	22.62	23.57	70- 80	55.05	776.2	96.9,96.9
90	0.2880	2.442	3.643	3.094	0.2599	0.9638	1.067	1.067	80- 90	13.57	789.7	98.6,98.6
100	0.6830	0.6944	0.7886	0.7058	0.5888	0.6428	0.6706	0.6421	90-100	0.8446	790.6	98.7,98.7
110	1.255	1.139	1.135	1.135	1.063	1.109	1.110	1.096	100-110	0.9357	791.5	98.9,98.9
120	1.812	1.650	1.653	1.660	1.625	1.585	1.590	1.574	110-120	1.368	792.9	99,99
130	2.288	2.117	2.105	2.143	2.099	2.037	2.013	2.013	120-130	1.675	794.5	99.2,99.2
140	2.689	2.524	2.490	2.559	2.501	2.429	2.372	2.398	130-140	1.779	796.3	99.5,99.5
150	2.999	2.892	2.832	2.932	2.821	2.765	2.676	2.738	140-150	1.672	798.0	99.7,99.7
160	3.242	3.209	3.217	3.222	3.116	3.064	3.038	3.059	150-160	1.380	799.4	99.8,99.8
170	3.535	3.511	3.552	3.498	3.438	3.405	3.422	3.401	160-170	0.9320	800.3	100,100
180	3.780	3.773	3.821	3.790	3.778	3.771	3.819	3.788	170-180	0.3423	800.7	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 434.63 lm

%lum = 54.3%

%lamp = 54.3%

Conical surface Flux(120deg): 621.94 lm

%lum = 77.7%


%lamp = 77.7%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	18563	28236
80	20347	26066
75	27168	31181
70	27684	30628
65	31005	33213
60	30864	32613
55	32646	34006
50	32325	33446
45	33379	34279


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Wall Exitance Coefficients(WEC)
0.0						
1.0	.308 .175 .056	.301 .172 .055	.287 .165 .053	.274 .158 .051	.262 .152 .049	
2.0	.291 .160 .049	.285 .157 .048	.272 .151 .047	.261 .146 .046	.250 .142 .045	
3.0	.270 .144 .043	.264 .141 .043	.253 .137 .042	.243 .133 .041	.233 .129 .040	
4.0	.249 .130 .038	.244 .128 .038	.234 .124 .037	.225 .121 .036	.217 .118 .036	
5.0	.231 .117 .034	.226 .116 .034	.217 .113 .033	.209 .110 .033	.201 .108 .032	
6.0	.214 .107 .031	.210 .106 .030	.202 .103 .030	.195 .101 .030	.188 .099 .029	
7.0	.199 .098 .028	.195 .097 .028	.188 .095 .027	.182 .093 .027	.176 .091 .027	
8.0	.186 .091 .026	.183 .090 .025	.176 .088 .025	.170 .086 .025	.165 .085 .025	
9.0	.174 .084 .024	.171 .083 .023	.166 .082 .023	.160 .080 .023	.155 .079 .023	
10.0	.164 .079 .022	.161 .078 .022	.156 .076 .022	.151 .075 .021	.146 .074 .021	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Ceiling Cavity Exitance Coefficients(CCEC)
0.0	.201 .201 .201	.172 .172 .172	.117 .117 .117	.067 .067 .067	.022 .022 .022	
1.0	.191 .167 .145	.163 .143 .125	.112 .098 .086	.064 .057 .050	.021 .018 .016	
2.0	.183 .142 .109	.157 .123 .094	.107 .085 .065	.062 .049 .038	.020 .016 .013	
3.0	.175 .125 .085	.150 .108 .074	.103 .075 .052	.060 .044 .030	.019 .014 .010	
4.0	.168 .112 .069	.144 .096 .060	.099 .067 .042	.057 .039 .025	.018 .013 .008	
5.0	.160 .101 .058	.138 .088 .050	.095 .061 .036	.055 .036 .021	.018 .012 .007	
6.0	.153 .093 .050	.132 .081 .043	.091 .056 .031	.053 .033 .018	.017 .011 .006	
7.0	.146 .086 .044	.126 .075 .038	.087 .052 .027	.050 .031 .016	.016 .010 .005	
8.0	.140 .080 .039	.120 .070 .034	.083 .049 .024	.048 .029 .015	.016 .009 .005	
9.0	.134 .075 .036	.115 .065 .031	.080 .046 .022	.046 .027 .013	.015 .009 .004	
10.0	.128 .071 .033	.110 .062 .029	.077 .043 .021	.045 .026 .012	.014 .008 .004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: 2835 IP20					TYPE: 2835 140LED 24V			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.: 0.008*0.5			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.7	27.3	26.0	27.5	27.7	25.9	27.5	26.2	27.7	27.9	
	3H	27.3	28.6	27.6	28.9	29.2	27.6	29.0	27.9	29.2	29.5
	4H	27.8	29.1	28.2	29.4	29.7	28.2	29.5	28.6	29.8	30.1
	6H	28.2	29.4	28.5	29.7	30.0	28.7	29.9	29.0	30.2	30.5
	8H	28.2	29.4	28.6	29.7	30.1	28.8	30.0	29.2	30.3	30.7
	12H	28.3	29.4	28.6	29.7	30.1	28.9	30.1	29.3	30.4	30.7
4H	2H	26.4	27.7	26.7	28.0	28.3	26.6	27.9	26.9	28.2	28.4
	3H	28.1	29.3	28.5	29.6	29.9	28.4	29.5	28.7	29.8	30.2
	4H	28.8	29.8	29.2	30.2	30.6	29.1	30.2	29.5	30.5	30.9
	6H	29.3	30.2	29.7	30.6	31.0	29.7	30.7	30.2	31.1	31.4
	8H	29.4	30.2	29.8	30.6	31.1	29.9	30.8	30.4	31.2	31.6
	12H	29.4	30.2	29.9	30.6	31.1	30.1	30.9	30.5	31.3	31.7
8H	4H	29.1	30.0	29.5	30.3	30.8	29.4	30.3	29.8	30.7	31.1
	6H	29.7	30.4	30.2	30.8	31.3	30.1	30.9	30.6	31.3	31.7
	8H	29.9	30.5	30.4	31.0	31.5	30.4	31.1	30.9	31.5	32.0
	12H	30.0	30.5	30.5	31.0	31.5	30.6	31.2	31.1	31.7	32.2
12H	4H	29.1	29.9	29.5	30.3	30.7	29.4	30.2	29.8	30.6	31.0
	6H	29.8	30.4	30.2	30.8	31.3	30.2	30.8	30.7	31.3	31.8
	8H	30.0	30.5	30.5	31.0	31.5	30.5	31.1	31.0	31.5	32.0
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.3					

CIE Pub.117, 800.7 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.8)
Area: 0.008 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) k(RI) x RCR = 5									
k = 0.60	57	45	38	56	45	38	55	44	38	31
0.80	67	55	48	66	55	48	64	54	47	40
1.00	75	64	57	74	64	56	72	65	56	49
1.25	82	72	65	81	71	64	78	70	63	56
1.50	88	78	71	86	77	70	83	75	69	61
2.00	94	86	79	93	85	79	89	82	77	69
2.50	98	91	85	96	89	84	92	86	82	73
3.00	102	95	89	100	93	88	95	90	86	77
4.00	106	100	95	103	98	94	99	95	91	82
5.00	108	103	99	106	101	98	101	98	94	85
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004										
Suspended										
SHRNOM = 1.25										

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity: 65.0%
 Test Distance: 5.749m [K=1.0000]
 Remarks:

AAI Figure

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

LED Avg.L Report

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	29775
L_0~180 (75) av	25032
L_0~180 (85) av	13939
L_90~270 (65) av	29772
L_90~270 (75) av	25217
L_90~270 (85) av	16422
L_45 (65) av	29604
L_45 (75) av	25202
L_45 (85) av	15705

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity: 65.0%
 Test Distance: 5.749m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

Table--1

UNIT: cd

C (DEG) □ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	271	271	271	271	271	271	271	271	271	271	271	271	271	271	271	271			
5	270	270	270	270	270	270	270	270	270	270	270	270	270	270	270	270			
10	266	267	267	267	267	267	267	267	266	266	266	265	265	265	265	266			
15	262	263	263	263	263	264	263	263	262	262	261	261	261	261	261	261			
20	253	254	255	255	255	255	255	254	253	253	252	251	251	251	252	252			
25	246	247	247	248	248	248	248	247	246	245	244	243	243	243	244	244			
30	232	233	234	235	235	235	234	234	232	231	230	229	229	229	230	230			
35	221	223	224	225	225	225	224	223	222	220	219	218	218	218	219	219			
40	203	205	206	207	207	207	206	205	203	201	200	199	199	199	200	201			
45	189	191	193	194	194	194	193	192	190	188	186	185	185	184	186	187			
50	166	169	170	172	172	172	171	170	167	165	163	162	161	161	162	164			
55	150	153	154	156	156	156	155	154	151	148	147	145	144	144	146	147			
60	124	127	129	131	130	131	129	128	125	119	118	118	118	117	119	120			
65	105	109	110	112	112	112	111	109	106	98.7	99.0	98.9	98.6	98.2	99.8	101			
70	75.9	79.6	81.5	83.8	83.7	83.9	82.3	80.5	76.8	70.1	71.4	69.5	69.1	68.8	70.3	72.0			
75	56.3	59.9	62.2	64.3	64.5	64.5	63.0	60.9	57.1	52.3	52.3	49.9	49.5	49.2	50.7	52.5			
80	28.3	31.7	33.8	36.0	36.2	36.2	34.6	32.6	28.4	25.9	24.8	22.9	22.6	22.4	23.6	25.0			
85	13.0	15.6	17.4	19.4	19.7	19.7	18.3	16.6	12.7	10.9	10.5	9.30	9.19	9.01	9.76	10.7			
90	0.29	1.60	2.44	3.40	3.64	3.68	3.09	2.31	0.26	0.91	0.96	0.95	1.07	1.10	1.07	0.88			
95	0.40	0.48	0.64	0.75	0.88	0.97	0.91	0.71	0.36	0.39	0.53	0.58	0.59	0.60	0.55	0.41			
100	0.68	0.63	0.69	0.78	0.79	0.78	0.71	0.65	0.59	0.61	0.64	0.66	0.67	0.67	0.64	0.62			
105	0.90	0.82	0.83	0.88	0.90	0.87	0.83	0.84	0.77	0.79	0.82	0.82	0.83	0.82	0.81	0.79			
110	1.25	1.13	1.14	1.13	1.14	1.13	1.14	1.15	1.06	1.09	1.11	1.11	1.11	1.11	1.10	1.07			
115	1.48	1.35	1.35	1.34	1.35	1.34	1.35	1.37	1.31	1.29	1.30	1.30	1.31	1.30	1.29	1.27			
120	1.81	1.67	1.65	1.65	1.65	1.65	1.66	1.69	1.62	1.60	1.58	1.59	1.59	1.59	1.57	1.57			
125	2.01	1.88	1.84	1.84	1.84	1.84	1.86	1.89	1.82	1.79	1.77	1.77	1.77	1.77	1.76	1.77			
130	2.29	2.18	2.12	2.10	2.10	2.12	2.14	2.20	2.10	2.07	2.04	2.02	2.01	2.02	2.01	2.05			
135	2.46	2.35	2.29	2.27	2.26	2.29	2.31	2.39	2.27	2.24	2.21	2.18	2.17	2.18	2.17	2.22			
140	2.69	2.60	2.52	2.49	2.49	2.54	2.56	2.64	2.50	2.47	2.43	2.41	2.37	2.39	2.40	2.46			
145	2.82	2.75	2.68	2.63	2.63	2.69	2.71	2.78	2.63	2.60	2.57	2.55	2.49	2.51	2.54	2.60			
150	3.00	2.95	2.89	2.83	2.83	2.91	2.93	2.98	2.82	2.79	2.76	2.75	2.68	2.70	2.74	2.79			
155	3.11	3.06	3.03	2.97	2.99	3.05	3.06	3.09	2.94	2.91	2.88	2.88	2.82	2.83	2.87	2.92			
160	3.24	3.25	3.21	3.16	3.22	3.23	3.22	3.25	3.12	3.09	3.06	3.07	3.04	3.02	3.06	3.11			
165	3.39	3.37	3.33	3.29	3.37	3.34	3.32	3.35	3.24	3.22	3.19	3.20	3.19	3.15	3.19	3.24			
170	3.53	3.53	3.51	3.49	3.55	3.51	3.50	3.52	3.44	3.42	3.40	3.41	3.42	3.38	3.40	3.45			
175	3.64	3.64	3.63	3.63	3.68	3.65	3.63	3.65	3.58	3.57	3.56	3.57	3.59	3.55	3.57	3.61			
180	3.78	3.77	3.77	3.78	3.82	3.79	3.79	3.80	3.78	3.77	3.77	3.79	3.82	3.79	3.79	3.80			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks: