


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 109.00 lm/W
MODEL	2700K	I _{max} (cd)	275.0	S/MH(C0/180)	1.28	
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.24	
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	810.87	<input type="checkbox"/> UP,DN(C0-180)	0.7,51.7	
NOMINAL FLUX(lm)	5.79196	CIE CLASS	DIRECT	<input type="checkbox"/> UP,DN(C180-360)	0.6,46.9	
LAMPS INSIDE	140	<input type="checkbox"/> up (%)	1.4	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	24	<input type="checkbox"/> down (%)	98.6	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity:65.0%
 Test Distance:5.749m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

°	C0	C45	C90	C135	C180	C225	C270	C315	°	zone	total	%lum, lamp
10	269.9	271.7	272.5	272.1	270.4	268.6	267.7	268.2	0- 10	26.00	26.00	3.21,3.21
20	256.4	259.9	261.5	260.6	257.3	253.7	251.9	252.9	10- 20	74.68	100.7	12.4,12.4
30	234.4	239.4	241.9	240.6	235.8	230.5	227.9	229.4	20- 30	113.8	214.5	26.5,26.5
40	204.4	210.9	214.1	212.6	206.4	199.7	196.3	198.1	30- 40	138.3	352.8	43.5,43.5
50	167.1	174.9	178.9	177.2	169.9	161.9	157.7	159.7	40- 50	144.7	497.5	61.4,61.4
60	123.4	132.5	137.2	135.4	126.9	117.8	113.0	115.1	50- 60	131.7	629.3	77.6,77.6
70	74.88	84.74	90.19	88.21	78.96	69.38	64.39	66.20	60- 70	100.2	729.5	90,90
80	27.00	36.12	41.67	39.74	30.21	23.10	19.86	20.54	70- 80	55.80	785.3	96.8,96.8
90	0.2965	3.490	6.536	5.207	0.2953	1.070	0.9299	0.7591	80- 90	14.49	799.8	98.6,98.6
100	0.6995	0.6181	0.6133	0.6105	0.5696	0.6380	0.7015	0.6778	90-100	1.048	800.8	98.8,98.8
110	1.264	1.105	1.062	1.086	1.051	1.099	1.163	1.132	100-110	0.9155	801.7	98.9,98.9
120	1.831	1.631	1.580	1.615	1.579	1.578	1.635	1.612	110-120	1.357	803.1	99,99
130	2.324	2.100	2.055	2.110	2.058	2.032	2.051	2.042	120-130	1.668	804.8	99.2,99.2
140	2.729	2.521	2.464	2.547	2.460	2.424	2.401	2.420	130-140	1.776	806.5	99.5,99.5
150	3.043	2.890	2.825	2.911	2.791	2.762	2.695	2.757	140-150	1.672	808.2	99.7,99.7
160	3.291	3.199	3.208	3.199	3.099	3.064	3.057	3.073	150-160	1.381	809.6	99.8,99.8
170	3.541	3.501	3.545	3.496	3.430	3.411	3.434	3.411	160-170	0.9318	810.5	100,100
180	3.789	3.777	3.828	3.796	3.786	3.777	3.824	3.796	170-180	0.3426	810.9	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 440.12 lm

%lum = 54.3%

%lamp = 54.3%

Conical surface Flux(120deg): 629.27 lm

%lum = 77.6%


%lamp = 77.6%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

° Range: 0 - 180DEG
° Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	16878	34989
80	19409	30014
75	26577	34144
70	27328	32985
65	30843	35205
60	30799	34336
55	32709	35536
50	32452	34822
45	33597	35535


C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity: 65.0%
 Test Distance: 5.749m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Wall Exitance Coefficients(WEC)
0.0						
1.0	.309 .176 .056	.302 .172 .055	.288 .165 .053	.275 .159 .051	.263 .152 .049	
2.0	.292 .160 .049	.285 .157 .048	.273 .152 .047	.261 .146 .046	.251 .142 .045	
3.0	.270 .144 .043	.264 .142 .043	.253 .137 .042	.243 .133 .041	.234 .129 .040	
4.0	.249 .130 .038	.244 .128 .038	.234 .124 .037	.225 .121 .036	.217 .118 .036	
5.0	.231 .117 .034	.226 .116 .034	.217 .113 .033	.209 .110 .033	.201 .108 .032	
6.0	.214 .107 .031	.210 .106 .030	.202 .103 .030	.195 .101 .030	.188 .099 .029	
7.0	.199 .098 .028	.195 .097 .028	.188 .095 .027	.182 .093 .027	.176 .091 .027	
8.0	.186 .091 .026	.183 .090 .025	.176 .088 .025	.170 .086 .025	.165 .085 .025	
9.0	.174 .084 .024	.171 .083 .023	.166 .082 .023	.160 .080 .023	.155 .079 .023	
10.0	.164 .078 .022	.161 .078 .022	.156 .076 .022	.151 .075 .021	.146 .074 .021	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Ceiling Cavity Exitance Coefficients(CCEC)
0.0	.201 .201 .201	.172 .172 .172	.117 .117 .117	.067 .067 .067	.022 .022 .022	
1.0	.191 .167 .145	.163 .143 .125	.112 .098 .086	.064 .057 .050	.021 .018 .016	
2.0	.183 .142 .109	.157 .123 .094	.107 .085 .065	.062 .049 .038	.020 .016 .013	
3.0	.175 .125 .085	.150 .108 .074	.103 .075 .052	.060 .044 .030	.019 .014 .010	
4.0	.168 .112 .069	.144 .096 .060	.099 .067 .042	.057 .039 .025	.018 .013 .008	
5.0	.160 .101 .058	.138 .088 .050	.095 .061 .036	.055 .036 .021	.018 .012 .007	
6.0	.153 .093 .050	.132 .081 .043	.091 .056 .031	.053 .033 .018	.017 .011 .006	
7.0	.146 .086 .044	.126 .075 .038	.087 .052 .027	.051 .031 .016	.016 .010 .005	
8.0	.140 .080 .039	.120 .070 .034	.083 .049 .024	.048 .029 .015	.016 .009 .005	
9.0	.134 .075 .036	.115 .065 .031	.080 .046 .022	.047 .027 .013	.015 .009 .004	
10.0	.128 .071 .033	.110 .062 .029	.077 .043 .021	.045 .026 .012	.014 .008 .004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: 2835 IP20					TYPE: 2835 140LED 24V			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.: 0.008*0.5			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.7	27.3	26.0	27.5	27.7	26.1	27.6	26.4	27.9	28.1	
	27.2	28.6	27.5	28.9	29.1	27.8	29.2	28.1	29.5	29.7	
	27.8	29.1	28.1	29.4	29.7	28.5	29.8	28.9	30.1	30.4	
	28.1	29.3	28.4	29.6	29.9	29.1	30.3	29.4	30.6	30.9	
	28.2	29.4	28.5	29.7	30.0	29.2	30.4	29.6	30.8	31.1	
	28.2	29.3	28.5	29.6	30.0	29.4	30.5	29.7	30.9	31.2	
4H 2H	26.4	27.8	26.8	28.0	28.3	26.7	28.1	27.1	28.3	28.6	
	28.1	29.3	28.5	29.6	29.9	28.6	29.8	29.0	30.1	30.4	
	28.8	29.8	29.2	30.2	30.5	29.4	30.5	29.8	30.8	31.2	
	29.2	30.2	29.6	30.5	30.9	30.1	31.1	30.5	31.4	31.8	
	29.3	30.2	29.8	30.6	31.0	30.4	31.2	30.8	31.6	32.0	
	29.4	30.2	29.8	30.6	31.0	30.5	31.4	31.0	31.8	32.2	
8H 4H	29.1	30.0	29.5	30.4	30.8	29.7	30.6	30.1	31.0	31.4	
	29.7	30.4	30.2	30.8	31.3	30.5	31.2	31.0	31.7	32.1	
	29.9	30.5	30.4	31.0	31.4	30.9	31.5	31.3	32.0	32.4	
	30.0	30.5	30.5	31.0	31.5	31.1	31.7	31.6	32.2	32.7	
12H 4H	29.1	29.9	29.6	30.3	30.8	29.7	30.5	30.1	30.9	31.3	
	29.8	30.4	30.3	30.9	31.3	30.6	31.2	31.0	31.7	32.1	
	30.0	30.5	30.5	31.0	31.5	30.9	31.5	31.4	32.0	32.5	
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 0.2 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.4					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.1 / - 0.3					

CIE Pub.117, 810.9 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.7)
Area: 0.008 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	57	45	38	56	45	38	55	44	38	31
0.80	67	55	48	66	55	48	64	54	47	40
1.00	75	64	57	74	63	56	72	65	56	49
1.25	82	72	65	81	71	64	78	70	63	56
1.50	88	78	70	86	77	70	83	75	69	61
2.00	94	86	79	92	85	78	89	82	77	69
2.50	98	91	84	96	89	83	92	86	81	73
3.00	102	95	89	100	93	88	95	90	86	77
4.00	106	100	95	103	98	94	99	95	91	82
5.00	108	103	99	106	101	98	101	97	94	85
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity: 65.0%
 Test Distance: 5.749m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

AAI Figure

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity:65.0%
 Test Distance:5.749m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

LED Avg.L Report

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	30014
L_0~180 (75) av	25235
L_0~180 (85) av	13713
L_90~270 (65) av	30045
L_90~270 (75) av	25670
L_90~270 (85) av	19134
L_45 (65) av	30048
L_45 (75) av	25464
L_45 (85) av	17102

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2022-03-22

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity: 65.0%
 Test Distance: 5.749m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

Table--1

UNIT: cd

C (DEG) □ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	275	275	275	275	275	275	275	275	275	275	275	275	275	275	275	275			
5	274	274	275	275	275	275	275	274	274	274	273	273	273	273	273	273			
10	270	271	272	272	273	273	272	271	270	269	269	268	268	268	268	269			
15	266	267	268	269	269	269	269	268	266	265	264	263	262	262	263	264			
20	256	258	260	261	262	262	261	259	257	255	254	252	252	252	253	254			
25	249	251	253	254	255	255	254	252	250	247	245	244	243	243	245	246			
30	234	237	239	241	242	242	241	239	236	233	231	228	228	228	229	231			
35	223	227	229	231	232	232	230	228	225	222	219	217	216	216	218	220			
40	204	208	211	213	214	214	213	210	206	203	200	197	196	196	198	201			
45	190	195	197	200	201	201	199	197	193	188	185	182	182	182	184	186			
50	167	172	175	178	179	179	177	174	170	165	162	159	158	158	160	162			
55	150	155	159	162	163	163	161	158	153	148	145	141	140	140	142	145			
60	123	129	132	136	137	138	135	132	127	121	118	114	113	113	115	118			
65	104	110	114	118	119	119	117	114	108	100	98.8	94.8	93.8	93.5	95.9	98.9			
70	74.9	80.6	84.7	88.9	90.2	90.7	88.2	84.8	79.0	71.3	69.4	65.6	64.4	64.1	66.2	69.2			
75	55.1	60.7	65.0	69.2	70.6	71.0	68.6	65.1	59.2	52.6	49.9	46.3	45.2	44.8	46.7	49.5			
80	27.0	32.0	36.1	40.2	41.7	42.0	39.7	36.2	30.2	25.2	23.1	20.6	19.9	19.4	20.5	22.5			
85	11.8	15.9	19.3	22.9	24.4	24.7	22.5	19.2	13.7	10.6	9.67	8.43	8.15	7.82	8.09	8.83			
90	0.30	1.78	3.49	5.49	6.54	6.65	5.21	3.23	0.30	0.87	1.07	0.98	0.93	0.82	0.76	0.65			
95	0.42	0.45	0.81	1.46	1.91	1.84	1.23	0.72	0.35	0.41	0.47	0.52	0.53	0.53	0.50	0.42			
100	0.70	0.63	0.62	0.62	0.61	0.61	0.61	0.62	0.57	0.60	0.64	0.68	0.70	0.70	0.68	0.64			
105	0.92	0.82	0.80	0.78	0.77	0.77	0.78	0.80	0.75	0.77	0.81	0.86	0.87	0.87	0.85	0.81			
110	1.26	1.14	1.11	1.07	1.06	1.07	1.09	1.12	1.05	1.05	1.10	1.14	1.16	1.16	1.13	1.10			
115	1.50	1.36	1.31	1.28	1.27	1.27	1.30	1.34	1.26	1.26	1.29	1.33	1.36	1.35	1.33	1.30			
120	1.83	1.69	1.63	1.60	1.58	1.59	1.62	1.66	1.58	1.56	1.58	1.61	1.64	1.63	1.61	1.59			
125	2.04	1.89	1.83	1.79	1.78	1.79	1.82	1.87	1.78	1.76	1.76	1.79	1.81	1.81	1.79	1.78			
130	2.32	2.19	2.10	2.06	2.06	2.08	2.11	2.17	2.06	2.04	2.03	2.04	2.05	2.06	2.04	2.06			
135	2.50	2.37	2.28	2.24	2.23	2.26	2.29	2.36	2.23	2.21	2.20	2.20	2.20	2.21	2.20	2.23			
140	2.73	2.62	2.52	2.47	2.46	2.51	2.55	2.60	2.46	2.45	2.42	2.42	2.40	2.41	2.42	2.46			
145	2.86	2.77	2.68	2.62	2.61	2.67	2.70	2.75	2.60	2.58	2.57	2.56	2.52	2.54	2.56	2.61			
150	3.04	2.96	2.89	2.83	2.83	2.90	2.91	2.95	2.79	2.77	2.76	2.76	2.70	2.73	2.76	2.80			
155	3.15	3.09	3.02	2.96	2.98	3.03	3.03	3.06	2.91	2.89	2.88	2.89	2.84	2.85	2.88	2.92			
160	3.29	3.25	3.20	3.15	3.21	3.21	3.20	3.23	3.10	3.08	3.06	3.08	3.06	3.04	3.07	3.12			
165	3.39	3.37	3.31	3.27	3.36	3.33	3.31	3.34	3.22	3.21	3.19	3.21	3.21	3.17	3.20	3.25			
170	3.54	3.53	3.50	3.48	3.55	3.51	3.50	3.52	3.43	3.42	3.41	3.42	3.43	3.39	3.41	3.46			
175	3.65	3.64	3.62	3.62	3.67	3.64	3.63	3.65	3.58	3.57	3.57	3.58	3.60	3.55	3.57	3.61			
180	3.79	3.78	3.78	3.79	3.83	3.80	3.80	3.82	3.79	3.78	3.78	3.79	3.82	3.80	3.80	3.82			

C Range: 0 - 360DEG

C Interval: 22.5DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:

Test Date:2022-03-22

□ Range: 0 - 180DEG

□ Interval: 2.0DEG

Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450

Humidity:65.0%

Test Distance:5.749m [K=1.0000]

Remarks: