


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.: 202-20009-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 104.94 lm/W
MODEL	4000K	I _{max} (cd)	178.9	S/MH(C0/180)	1.28	
NOMINAL POWER(W)	4.8	LOR(%)	100.0	S/MH(C90/270)	1.28	
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	529.87	□ UP,DN(C0-180)	0.7,49.1	
NOMINAL FLUX(lm)	7.56959	CIE CLASS	DIRECT	□ UP,DN(C180-360)	0.6,49.6	
LAMPS INSIDE	70	□ up (%)	1.3	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	24	□ down (%)	98.7	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2022-03-16

□ Range: 0 - 180DEG
 □ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity:65.0%
 Test Distance:5.749m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	175.9	175.8	175.9	176.2	176.3	176.4	176.3	176.0	0- 10	16.95	16.95	3.2,3.2
20	167.3	167.2	167.3	167.8	168.1	168.2	168.1	167.6	10- 20	48.73	65.68	12.4,12.4
30	153.2	153.0	153.2	153.9	154.3	154.6	154.4	153.7	20- 30	74.41	140.1	26.4,26.4
40	133.9	133.7	133.8	134.7	135.3	135.7	135.6	134.7	30- 40	90.63	230.7	43.5,43.5
50	109.8	109.5	109.6	110.6	111.2	111.9	111.8	110.8	40- 50	95.03	325.7	61.5,61.5
60	81.38	80.95	81.07	82.10	82.59	83.48	83.60	82.46	50- 60	86.56	412.3	77.8,77.8
70	49.75	49.21	49.34	50.29	50.60	51.61	51.94	50.76	60- 70	65.83	478.1	90.2,90.2
80	18.69	18.03	17.97	18.86	17.77	19.93	20.22	19.37	70- 80	36.23	514.4	97.1,97.1
90	0.1860	0.6821	0.5994	0.7107	0.1573	0.7804	0.7418	0.6613	80- 90	8.550	522.9	98.7,98.7
100	0.4474	0.4469	0.4681	0.4440	0.3647	0.3524	0.3875	0.3639	90-100	0.4189	523.3	98.8,98.8
110	0.8095	0.7871	0.7887	0.7767	0.6887	0.6522	0.6563	0.6633	100-110	0.5923	523.9	98.9,98.9
120	1.186	1.130	1.129	1.124	1.032	0.9615	0.9629	0.9722	110-120	0.8824	524.8	99,99
130	1.512	1.432	1.433	1.444	1.346	1.271	1.253	1.269	120-130	1.088	525.9	99.2,99.2
140	1.774	1.696	1.678	1.718	1.608	1.540	1.502	1.526	130-140	1.160	527.0	99.5,99.5
150	1.970	1.920	1.903	1.941	1.822	1.766	1.709	1.761	140-150	1.092	528.1	99.7,99.7
160	2.141	2.110	2.132	2.117	2.020	1.973	1.954	1.973	150-160	0.9007	529.0	99.8,99.8
170	2.306	2.298	2.331	2.300	2.242	2.210	2.223	2.210	160-170	0.6077	529.6	100,100
180	2.470	2.462	2.493	2.471	2.468	2.460	2.491	2.471	170-180	0.2234	529.9	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 288.02 lm

%lum = 54.4%

%lamp = 54.4%

Conical surface Flux(120deg): 412.3 lm

%lum = 77.8%


%lamp = 77.8%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2022-03-16

□ Range: 0 - 180DEG
 □ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity:65.0%
 Test Distance:5.749m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.: 202-20009-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	12532	11430
80	13434	12942
75	17747	17540
70	18153	18042
65	20398	20343
60	20313	20280
55	21525	21519
50	21325	21330
45	22033	22056


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.: 202-20009-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															
	Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.04	.99	.96	1.01	.97	.94	.97	.94	.91	.93	.90	.88	.89	.87	.85	.83
2.0	.90	.83	.78	.88	.82	.77	.84	.79	.75	.81	.77	.73	.78	.74	.71	.69
3.0	.79	.71	.64	.77	.70	.64	.74	.68	.62	.71	.66	.61	.69	.64	.60	.58
4.0	.70	.61	.54	.69	.60	.54	.66	.59	.53	.63	.57	.52	.61	.56	.51	.49
5.0	.62	.53	.47	.61	.53	.46	.59	.51	.46	.57	.50	.45	.55	.49	.44	.42
6.0	.56	.47	.41	.55	.47	.40	.53	.46	.40	.51	.45	.39	.50	.44	.39	.37
7.0	.51	.42	.36	.50	.42	.36	.48	.41	.35	.47	.40	.35	.45	.39	.35	.33
8.0	.46	.38	.32	.46	.37	.32	.44	.37	.31	.43	.36	.31	.41	.35	.31	.29
9.0	.42	.34	.29	.42	.34	.29	.41	.33	.28	.39	.33	.28	.38	.32	.28	.26
10.0	.39	.31	.26	.39	.31	.26	.37	.30	.26	.36	.30	.25	.35	.30	.25	.24



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-16

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.: 202-20009-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Wall Exitance Coefficients(WEC)
0.0						
1.0	.308 .175 .055	.300 .171 .054	.286 .164 .052	.273 .158 .051	.261 .151 .049	
2.0	.291 .159 .049	.284 .157 .048	.272 .151 .047	.260 .146 .046	.250 .141 .045	
3.0	.270 .144 .043	.264 .141 .043	.253 .137 .042	.243 .133 .041	.233 .129 .040	
4.0	.249 .129 .038	.244 .128 .038	.234 .124 .037	.225 .121 .036	.217 .118 .036	
5.0	.230 .117 .034	.226 .116 .034	.217 .113 .033	.209 .110 .033	.201 .108 .032	
6.0	.214 .107 .031	.210 .106 .030	.202 .103 .030	.195 .101 .030	.188 .099 .029	
7.0	.199 .098 .028	.195 .097 .028	.188 .095 .027	.182 .093 .027	.176 .091 .027	
8.0	.186 .091 .026	.183 .090 .025	.176 .088 .025	.170 .086 .025	.165 .085 .025	
9.0	.174 .084 .024	.171 .083 .023	.166 .082 .023	.160 .080 .023	.155 .079 .023	
10.0	.164 .079 .022	.161 .078 .022	.156 .076 .022	.151 .075 .021	.147 .074 .021	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Ceiling Cavity Exitance Coefficients(CCEC)
0.0	.200 .200 .200	.171 .171 .171	.117 .117 .117	.067 .067 .067	.021 .021 .021	
1.0	.190 .166 .145	.163 .143 .124	.111 .098 .086	.064 .057 .050	.021 .018 .016	
2.0	.182 .142 .108	.156 .122 .094	.107 .085 .065	.062 .049 .038	.020 .016 .012	
3.0	.175 .125 .085	.150 .107 .073	.103 .075 .051	.059 .044 .030	.019 .014 .010	
4.0	.167 .111 .069	.143 .096 .060	.099 .067 .042	.057 .039 .025	.018 .013 .008	
5.0	.160 .101 .057	.137 .087 .050	.094 .061 .035	.055 .036 .021	.018 .012 .007	
6.0	.153 .093 .049	.131 .080 .043	.091 .056 .030	.053 .033 .018	.017 .011 .006	
7.0	.146 .086 .044	.125 .074 .038	.087 .052 .027	.050 .031 .016	.016 .010 .005	
8.0	.139 .080 .039	.120 .069 .034	.083 .049 .024	.048 .029 .014	.016 .009 .005	
9.0	.133 .075 .036	.115 .065 .031	.080 .046 .022	.046 .027 .013	.015 .009 .004	
10.0	.128 .071 .033	.110 .061 .029	.076 .043 .020	.045 .026 .012	.014 .008 .004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: 2835 IP20					TYPE: 2835 140LED 24V			WEIGHT:			
SPEC.: 202-20009-00					DIM.:			SERIAL No.:			
MFR.:					SUR.: 0.008*0.5			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.6	27.1	25.9	27.3	27.6	25.6	27.1	25.9	27.3	27.6	
	27.1	28.5	27.4	28.7	29.0	27.1	28.5	27.4	28.7	29.0	
	27.6	29.0	28.0	29.2	29.5	27.6	28.9	27.9	29.2	29.5	
	28.0	29.2	28.3	29.5	29.8	27.9	29.2	28.3	29.5	29.8	
	28.1	29.3	28.4	29.6	29.9	28.0	29.2	28.4	29.5	29.8	
	28.1	29.2	28.4	29.5	29.9	28.0	29.2	28.4	29.5	29.8	
4H 2H	26.2	27.5	26.5	27.8	28.1	26.2	27.5	26.5	27.8	28.1	
	27.9	29.0	28.2	29.3	29.7	27.8	29.0	28.2	29.3	29.7	
	28.5	29.6	28.9	29.9	30.3	28.5	29.5	28.9	29.9	30.3	
	29.0	29.9	29.4	30.3	30.7	28.9	29.9	29.3	30.2	30.6	
	29.1	30.0	29.5	30.3	30.8	29.0	29.9	29.5	30.3	30.7	
	29.1	29.9	29.6	30.3	30.8	29.1	29.9	29.5	30.3	30.7	
8H 4H	28.7	29.6	29.2	30.0	30.4	28.7	29.6	29.1	30.0	30.4	
	29.3	30.0	29.8	30.5	30.9	29.3	30.0	29.7	30.4	30.9	
	29.5	30.1	30.0	30.6	31.1	29.4	30.1	29.9	30.5	31.0	
	29.6	30.1	30.1	30.6	31.1	29.5	30.1	30.0	30.5	31.0	
12H 4H	28.7	29.5	29.2	29.9	30.4	28.7	29.5	29.2	29.9	30.4	
	29.3	30.0	29.8	30.4	30.9	29.3	29.9	29.8	30.4	30.9	
	29.5	30.1	30.0	30.6	31.1	29.5	30.0	30.0	30.5	31.0	
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 529.9 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.2)
Area: 0.008 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:


```

Range: 0 - 180DEG
Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

```

ISOCANDELA DIAGRAM

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.: 202-20009-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

AAI Figure

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.: 202-20009-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2022-03-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity:65.0%
 Test Distance:5.749m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.: 202-20009-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

LED Avg.L Report

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.: 202-20009-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	19640
L_0~180 (75) av	16375
L_0~180 (85) av	8984
L_90~270 (65) av	19767
L_90~270 (75) av	16602
L_90~270 (85) av	9564
L_45 (65) av	19727
L_45 (75) av	16526
L_45 (85) av	10026

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-03-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2022-03-16

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity: 65.0%
 Test Distance: 5.749m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 2835 IP20	TYPE: 2835 140LED 24V	WEIGHT:
SPEC.: 202-20009-00	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.008*0.5	Shielding Angle:

Table--1

UNIT: cd

C (DEG) □ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	179	179	179	179	179	179	179	179	179	179	179	179	179	179	179	179			
5	178	178	178	178	178	178	178	179	179	179	179	179	179	179	178	178			
10	176	176	176	176	176	176	176	176	176	176	176	176	176	176	176	176			
15	173	173	173	173	173	173	173	174	174	174	174	174	174	173	173	173			
20	167	167	167	167	167	168	168	168	168	168	168	168	168	168	168	167			
25	162	162	162	162	162	163	163	163	163	163	163	163	163	163	163	162			
30	153	153	153	153	153	154	154	154	154	154	155	154	154	154	154	153			
35	146	146	146	146	146	147	147	147	147	147	148	147	147	147	147	146			
40	134	134	134	134	134	134	135	135	135	135	136	135	136	135	135	134			
45	125	125	125	125	125	125	126	126	126	126	127	126	127	126	126	125			
50	110	110	109	110	110	110	111	111	111	111	112	112	112	111	111	110			
55	98.9	99.1	98.5	98.9	98.7	99.5	99.7	100	100	100	101	101	101	100	100.0	99.1			
60	81.4	81.5	80.9	81.3	81.1	81.9	82.1	82.6	82.6	82.7	83.5	83.3	83.6	82.8	82.5	81.5			
65	69.1	69.1	68.6	68.9	68.7	69.5	69.7	70.2	70.1	70.3	71.1	71.0	71.3	70.6	70.1	69.3			
70	49.7	49.7	49.2	49.6	49.3	50.0	50.3	50.8	50.6	50.8	51.6	51.6	51.9	51.3	50.8	49.9			
75	36.8	36.7	36.2	36.5	36.3	37.0	37.2	37.7	37.5	37.7	38.5	38.5	38.9	38.2	37.8	36.9			
80	18.7	18.6	18.0	18.2	18.0	18.6	18.9	19.3	17.8	19.3	19.9	19.9	20.2	19.7	19.4	18.7			
85	8.75	8.78	8.36	8.27	7.97	8.53	8.92	9.28	7.74	9.23	9.68	9.47	9.67	9.37	9.36	8.86			
90	0.19	0.68	0.68	0.66	0.60	0.66	0.71	0.66	0.16	0.60	0.78	0.75	0.74	0.67	0.66	0.57			
95	0.26	0.28	0.38	0.42	0.43	0.45	0.43	0.27	0.22	0.23	0.33	0.36	0.35	0.35	0.33	0.24			
100	0.45	0.44	0.45	0.46	0.47	0.46	0.44	0.43	0.36	0.35	0.35	0.36	0.39	0.37	0.36	0.36			
105	0.59	0.57	0.58	0.58	0.59	0.58	0.57	0.56	0.49	0.47	0.47	0.47	0.47	0.48	0.48	0.48			
110	0.81	0.78	0.79	0.79	0.79	0.79	0.78	0.77	0.69	0.65	0.65	0.65	0.66	0.66	0.66	0.67			
115	0.96	0.92	0.93	0.93	0.93	0.92	0.92	0.92	0.82	0.78	0.78	0.78	0.78	0.78	0.78	0.79			
120	1.19	1.13	1.13	1.13	1.13	1.13	1.12	1.13	1.03	0.98	0.96	0.96	0.96	0.97	0.97	0.99			
125	1.33	1.27	1.26	1.25	1.26	1.26	1.26	1.27	1.17	1.11	1.09	1.09	1.09	1.09	1.10	1.11			
130	1.51	1.46	1.43	1.43	1.43	1.44	1.44	1.46	1.35	1.30	1.27	1.26	1.25	1.26	1.27	1.30			
135	1.62	1.58	1.54	1.54	1.54	1.55	1.56	1.59	1.46	1.42	1.38	1.37	1.36	1.36	1.37	1.42			
140	1.77	1.73	1.70	1.68	1.68	1.71	1.72	1.73	1.61	1.57	1.54	1.52	1.50	1.51	1.53	1.58			
145	1.86	1.83	1.79	1.76	1.77	1.81	1.82	1.83	1.70	1.66	1.63	1.62	1.59	1.60	1.63	1.67			
150	1.97	1.95	1.92	1.89	1.90	1.95	1.94	1.95	1.82	1.79	1.77	1.75	1.71	1.73	1.76	1.80			
155	2.04	2.03	2.00	1.97	2.00	2.03	2.02	2.02	1.90	1.87	1.85	1.84	1.81	1.82	1.85	1.88			
160	2.14	2.13	2.11	2.09	2.13	2.13	2.12	2.13	2.02	1.99	1.97	1.97	1.95	1.94	1.97	2.01			
165	2.20	2.20	2.18	2.17	2.22	2.20	2.19	2.20	2.10	2.08	2.06	2.06	2.06	2.03	2.06	2.10			
170	2.31	2.31	2.30	2.29	2.33	2.31	2.30	2.31	2.24	2.23	2.21	2.21	2.22	2.19	2.21	2.25			
175	2.38	2.38	2.37	2.38	2.41	2.39	2.38	2.39	2.34	2.33	2.32	2.32	2.33	2.30	2.32	2.35			
180	2.47	2.46	2.46	2.47	2.49	2.47	2.47	2.49	2.47	2.46	2.46	2.47	2.49	2.47	2.47	2.49			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-03-16

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks: