


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: 2835 IP67	TYPE: 128LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.012*0.5	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 109.68 lm/W
MODEL	2700K RA90 12MM 9.6W	I _{max} (cd)	75.54	S/MH (C0/180)	1.24	
NOMINAL POWER(W)	2.4	LOR (%)	100.0	S/MH (C90/270)	1.30	
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	264.01	□ UP, DN (C0-180)	5.5, 46.2	
NOMINAL FLUX(lm)	8.25027	CIE CLASS	DIRECT	□ UP, DN (C180-360)	2.3, 46.0	
LAMPS INSIDE	32	□ up (%)	7.8	CIBSE SHR NOM	1.50	
TEST VOLTAGE (V)	24	□ down (%)	92.2	CIBSE SHR MAX	1.50	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT: lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-04-14

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	74.95	75.15	74.86	74.12	73.48	74.00	74.76	75.08	0- 10	7.158	7.158	2.71,2.71
20	71.99	72.34	71.44	70.41	69.25	70.46	71.64	72.47	10- 20	20.68	27.84	10.5,10.5
30	66.61	66.89	65.41	64.23	62.95	64.51	65.89	67.27	20- 30	31.67	59.51	22.5,22.5
40	58.89	59.09	57.43	55.94	54.66	56.39	57.90	59.65	30- 40	38.66	98.17	37.2,37.2
50	48.94	49.49	47.75	46.09	44.59	46.51	48.25	50.16	40- 50	40.80	139.0	52.6,52.6
60	36.96	38.26	37.28	35.09	33.06	35.54	37.97	39.19	50- 60	37.88	176.8	67,67
70	23.23	28.94	34.71	25.09	20.47	25.38	34.00	29.63	60- 70	31.54	208.4	78.9,78.9
80	8.235	18.35	20.02	16.95	7.887	16.93	20.67	19.07	70- 80	24.10	232.5	88.1,88.1
90	0.0856	6.620	8.375	6.417	0.0857	6.110	8.364	6.747	80- 90	10.83	243.3	92.2,92.2
100	0.1878	6.034	7.330	6.064	0.1833	4.921	6.737	5.304	90-100	5.377	248.7	94.2,94.2
110	0.3377	5.743	7.166	5.780	0.3262	2.043	4.793	2.415	100-110	4.344	253.0	95.8,95.8
120	0.4853	5.388	7.042	5.468	0.4784	0.4663	2.198	0.4328	110-120	3.066	256.1	97,97
130	0.6161	5.528	7.521	5.764	0.6069	0.5710	0.5540	0.5422	120-130	2.341	258.4	97.9,97.9
140	0.7280	6.316	9.250	6.893	0.7116	0.6709	0.6396	0.6372	130-140	2.195	260.6	98.7,98.7
150	0.8113	4.488	11.24	4.852	0.7853	0.7565	0.7109	0.7229	140-150	2.000	262.6	99.5,99.5
160	0.8875	1.010	3.178	1.198	0.8615	0.8326	0.8061	0.8132	150-160	0.9901	263.6	99.9,99.9
170	0.9660	0.9609	0.9772	0.9675	0.9519	0.9325	0.9178	0.9178	160-170	0.2858	263.9	100,100
180	1.045	1.037	1.044	1.041	1.045	1.037	1.041	1.039	170-180	0.0937	264.0	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 122.72 lm

%lum = 46.5%

%lamp = 46.5%

Conical surface Flux(120deg): 176.85 lm

%lum = 67.0%


%lamp = 67.0%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-04-14

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

NAME: 2835 IP67	TYPE: 128LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.012*0.5	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	243	13434
80	3950	9609
75	5630	9740
70	5656	8459
65	6235	6798
60	6156	6215
55	6445	6328
50	6342	6192
45	6499	6336


C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2022-04-14

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity: 65.0%
 Test Distance: 5.749m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: 2835 IP67	TYPE: 128LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.012*0.5	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.17	1.17	1.17	1.14	1.14	1.14	1.07	1.07	1.07	1.01	1.01	1.01	.95	.95	.95	.92
1.0	1.00	.95	.91	.97	.93	.89	.91	.88	.85	.86	.83	.81	.81	.79	.77	.74
2.0	.86	.79	.73	.84	.77	.71	.79	.73	.68	.74	.70	.66	.70	.66	.63	.60
3.0	.75	.67	.60	.73	.65	.59	.69	.62	.57	.65	.59	.55	.62	.57	.53	.50
4.0	.66	.57	.50	.65	.56	.49	.61	.54	.48	.58	.51	.46	.55	.49	.45	.42
5.0	.59	.50	.43	.58	.49	.42	.54	.47	.41	.52	.45	.40	.49	.43	.39	.36
6.0	.53	.44	.37	.52	.43	.37	.49	.41	.36	.47	.40	.35	.44	.39	.34	.32
7.0	.48	.39	.33	.47	.38	.32	.45	.37	.32	.42	.36	.31	.40	.35	.30	.28
8.0	.44	.35	.29	.43	.34	.29	.41	.33	.28	.39	.32	.27	.37	.31	.27	.25
9.0	.40	.32	.26	.39	.31	.26	.37	.30	.25	.36	.29	.25	.34	.28	.24	.22
10.0	.37	.29	.24	.36	.28	.23	.35	.28	.23	.33	.27	.22	.32	.26	.22	.20



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-04-14

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: 2835 IP67	TYPE: 128LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.012*0.5	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Wall Exitance Coefficients(WEC)
0.0						
1.0	.346 .197 .062	.336 .192 .061	.318 .183 .058	.302 .174 .056	.287 .166 .054	
2.0	.313 .172 .053	.304 .168 .052	.288 .160 .050	.274 .154 .048	.260 .147 .046	
3.0	.284 .151 .045	.276 .148 .045	.262 .142 .043	.249 .136 .042	.236 .131 .040	
4.0	.259 .134 .040	.252 .132 .039	.239 .127 .038	.227 .122 .037	.216 .117 .036	
5.0	.237 .121 .035	.231 .118 .035	.219 .114 .034	.208 .110 .033	.198 .106 .032	
6.0	.218 .109 .031	.213 .108 .031	.202 .104 .030	.193 .100 .029	.183 .097 .029	
7.0	.202 .100 .028	.197 .098 .028	.188 .095 .027	.179 .092 .027	.171 .089 .026	
8.0	.188 .092 .026	.184 .090 .026	.175 .087 .025	.167 .085 .024	.159 .082 .024	
9.0	.176 .085 .024	.172 .084 .023	.164 .081 .023	.156 .078 .022	.149 .076 .022	
10.0	.165 .079 .022	.161 .078 .022	.154 .075 .021	.147 .073 .021	.141 .071 .020	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Ceiling Cavity Exitance Coefficients(CCEC)
0.0	.250 .250 .250	.214 .214 .214	.146 .146 .146	.084 .084 .084	.027 .027 .027	
1.0	.243 .216 .192	.208 .185 .165	.142 .128 .114	.082 .074 .066	.026 .024 .021	
2.0	.236 .192 .156	.202 .166 .135	.138 .115 .094	.080 .067 .055	.026 .022 .018	
3.0	.228 .175 .133	.196 .151 .116	.134 .105 .081	.078 .061 .048	.025 .020 .016	
4.0	.220 .162 .118	.189 .140 .103	.130 .098 .072	.075 .057 .043	.024 .019 .014	
5.0	.213 .152 .108	.183 .132 .094	.126 .092 .066	.073 .054 .039	.023 .018 .013	
6.0	.205 .144 .100	.177 .125 .087	.122 .087 .062	.071 .051 .037	.023 .017 .012	
7.0	.198 .137 .094	.171 .119 .082	.118 .083 .058	.069 .049 .035	.022 .016 .011	
8.0	.192 .132 .090	.165 .114 .079	.114 .080 .056	.066 .047 .033	.022 .016 .011	
9.0	.186 .127 .087	.160 .110 .076	.111 .077 .054	.065 .046 .032	.021 .015 .011	
10.0	.180 .123 .084	.155 .106 .074	.108 .075 .052	.063 .044 .031	.020 .015 .010	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-04-14

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: 2835 IP67					TYPE: 128LED 24V			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.: 0.012*0.5			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	23.5	24.9	23.8	25.3	25.6	23.5	24.9	23.8	25.3	25.6	
	25.0	26.4	25.5	26.8	27.2	26.0	27.3	26.4	27.7	28.1	
	25.7	27.0	26.1	27.4	27.8	27.3	28.6	27.7	29.0	29.4	
	26.2	27.4	26.6	27.8	28.2	28.3	29.5	28.7	29.9	30.3	
	26.2	27.3	26.6	27.8	28.2	28.7	29.9	29.1	30.3	30.7	
	26.1	27.2	26.6	27.7	28.2	29.1	30.2	29.5	30.6	31.1	
4H	2H	24.1	25.4	24.6	25.8	26.2	24.2	25.4	24.6	25.8	26.3
	3H	26.0	27.1	26.5	27.6	28.0	26.9	28.1	27.4	28.5	29.0
	4H	26.8	27.9	27.3	28.3	28.8	28.4	29.4	28.9	29.9	30.4
	6H	27.5	28.4	28.0	28.9	29.4	29.6	30.5	30.1	31.0	31.5
	8H	27.6	28.4	28.1	28.9	29.5	30.0	30.9	30.6	31.4	32.0
	12H	27.6	28.4	28.1	28.9	29.5	30.5	31.3	31.0	31.8	32.4
8H	4H	27.5	28.4	28.0	28.9	29.4	28.8	29.6	29.3	30.1	30.7
	6H	28.4	29.1	29.0	29.7	30.3	30.2	30.9	30.7	31.4	32.0
	8H	28.6	29.3	29.2	29.8	30.5	30.8	31.4	31.4	32.0	32.6
	12H	28.8	29.3	29.4	29.9	30.5	31.4	32.0	32.0	32.5	33.2
12H	4H	27.6	28.4	28.2	28.9	29.5	28.8	29.6	29.3	30.1	30.7
	6H	28.6	29.3	29.2	29.8	30.5	30.3	30.9	30.8	31.5	32.1
	8H	29.0	29.5	29.6	30.1	30.8	31.0	31.5	31.6	32.1	32.7
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.1 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.1 / - 0.3					+ 0.1 / - 0.2					

CIE Pub.117, 264.0 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -4.6)
Area: 0.012 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-04-14

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:


```

Range: 0 - 180DEG
Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

```

ISOCANDELA DIAGRAM

NAME: 2835 IP67	TYPE: 128LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.012*0.5	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-04-14

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

AAI Figure

NAME: 2835 IP67	TYPE: 128LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.012*0.5	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-04-14

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

NAME: 2835 IP67	TYPE: 128LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.012*0.5	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-04-14

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

LED Avg.L Report

NAME: 2835 IP67	TYPE: 128LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.012*0.5	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	5636
L_0~180 (75) av	4845
L_0~180 (85) av	1242
L_90~270 (65) av	6800
L_90~270 (75) av	9185
L_90~270 (85) av	12227
L_45 (65) av	6190
L_45 (75) av	7974
L_45 (85) av	10221

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-04-14

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2022-04-14

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 2835 IP67	TYPE: 128LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.012*0.5	Shielding Angle:

Table--1

UNIT: cd

C (DEG) □ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4			
5	75.5	75.5	75.5	75.5	75.4	75.2	75.1	75.0	74.9	74.9	75.0	75.1	75.3	75.4	75.4	75.5			
10	74.9	75.1	75.1	75.1	74.9	74.5	74.1	73.7	73.5	73.6	74.0	74.4	74.8	75.0	75.1	75.0			
15	74.1	74.3	74.4	74.2	73.8	73.5	73.0	72.4	72.1	72.3	72.9	73.4	73.9	74.2	74.4	74.2			
20	72.0	72.4	72.3	72.0	71.4	71.0	70.4	69.8	69.3	69.7	70.5	71.0	71.6	72.1	72.5	72.3			
25	70.1	70.6	70.5	70.0	69.2	68.8	68.2	67.7	67.0	67.6	68.3	69.0	69.7	70.3	70.7	70.6			
30	66.6	67.2	66.9	66.2	65.4	64.8	64.2	63.8	62.9	63.7	64.5	65.1	65.9	66.6	67.3	67.2			
35	63.8	64.4	64.0	63.4	62.4	61.7	61.1	60.8	59.9	60.7	61.5	62.0	62.9	63.7	64.5	64.5			
40	58.9	59.6	59.1	58.5	57.4	56.6	55.9	55.6	54.7	55.5	56.4	56.9	57.9	58.8	59.6	59.6			
45	55.2	55.9	55.5	54.8	53.7	52.9	52.2	51.8	50.8	51.7	52.6	53.1	54.2	55.2	56.1	56.0			
50	48.9	49.7	49.5	48.9	47.7	46.9	46.1	45.6	44.6	45.5	46.5	47.1	48.3	49.3	50.2	49.9			
55	44.4	45.2	45.1	44.6	43.5	42.7	41.8	41.2	40.1	41.2	42.2	42.9	44.1	45.2	45.9	45.5			
60	37.0	37.9	38.3	38.1	37.3	36.2	35.1	34.2	33.1	34.3	35.5	36.5	38.0	38.9	39.2	38.4			
65	31.6	32.8	33.6	34.5	34.5	32.4	30.6	29.4	28.2	29.5	31.1	32.7	35.0	35.5	34.7	33.3			
70	23.2	24.9	28.9	34.1	34.7	31.3	25.1	22.1	20.5	22.3	25.4	31.0	34.0	33.6	29.6	25.6			
75	17.5	20.6	27.3	30.1	30.2	29.1	24.2	17.6	15.3	17.8	23.8	28.2	29.8	29.7	27.1	21.2			
80	8.24	14.2	18.4	20.2	20.0	19.2	17.0	13.0	7.89	12.6	16.9	19.4	20.7	20.6	19.1	14.5			
85	0.25	8.95	12.4	14.0	14.0	13.3	11.2	8.05	3.60	7.64	11.2	13.0	14.2	14.2	13.1	9.22			
90	0.09	3.74	6.62	8.11	8.38	7.89	6.42	3.67	0.09	3.31	6.11	7.66	8.36	8.18	6.75	3.80			
95	0.12	3.32	5.81	7.07	7.44	7.15	5.89	3.46	0.11	3.02	5.53	6.81	7.10	6.84	5.63	3.17			
100	0.19	3.36	6.03	7.06	7.33	7.07	6.06	3.61	0.18	1.41	4.92	6.48	6.74	6.46	5.30	1.87			
105	0.24	3.30	6.05	7.02	7.27	7.03	6.12	3.54	0.24	0.36	2.78	5.91	6.34	5.93	4.29	0.54			
110	0.34	2.88	5.74	6.89	7.17	6.86	5.78	3.10	0.33	0.33	2.04	3.93	4.79	4.25	2.41	0.30			
115	0.40	2.60	5.60	6.78	7.03	6.74	5.63	2.80	0.39	0.38	0.90	2.41	3.82	3.24	1.10	0.34			
120	0.49	2.30	5.39	6.76	7.04	6.76	5.47	2.55	0.48	0.46	0.47	0.96	2.20	1.34	0.43	0.42			
125	0.54	2.15	5.36	6.78	7.11	6.81	5.44	2.52	0.53	0.51	0.51	0.52	0.72	0.51	0.48	0.47			
130	0.62	1.86	5.53	7.12	7.52	7.28	5.76	2.48	0.61	0.58	0.57	0.57	0.55	0.55	0.54	0.54			
135	0.67	1.68	5.68	7.48	8.02	7.67	5.91	2.30	0.65	0.63	0.62	0.60	0.59	0.58	0.58	0.58			
140	0.73	1.25	6.32	8.54	9.25	8.85	6.89	1.99	0.71	0.69	0.67	0.66	0.64	0.63	0.64	0.65			
145	0.76	0.90	6.47	9.60	10.5	10.00	6.83	1.46	0.75	0.72	0.71	0.69	0.67	0.67	0.67	0.69			
150	0.81	0.83	4.49	9.67	11.2	9.00	4.85	0.92	0.79	0.77	0.76	0.74	0.71	0.72	0.72	0.74			
155	0.84	0.84	2.41	6.83	8.77	6.56	2.90	0.88	0.82	0.80	0.79	0.77	0.75	0.75	0.76	0.77			
160	0.89	0.89	1.01	2.38	3.18	2.56	1.20	0.91	0.86	0.85	0.83	0.82	0.81	0.80	0.81	0.83			
165	0.92	0.92	0.92	1.19	1.49	1.28	0.95	0.93	0.90	0.88	0.87	0.86	0.85	0.84	0.85	0.87			
170	0.97	0.97	0.96	0.96	0.98	0.97	0.97	0.98	0.95	0.94	0.93	0.92	0.92	0.91	0.92	0.93			
175	1.00	1.01	1.00	0.99	1.01	1.00	1.00	1.01	0.99	0.98	0.98	0.97	0.96	0.96	0.97	0.98			
180	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.05	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.05			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2022-04-14

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks: