


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: 2835 IP20	TYPE: 2835 160LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 129.71 lm/W
MODEL	6500K	I <sub>max</sub> (cd)	146.1	S/MH(C0/180)	1.30	
NOMINAL POWER(W)	3.6	LOR(%)	100.0	S/MH(C90/270)	1.29	
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	441.72	<input type="checkbox"/> UP,DN(C0-180)	0.7,49.1	
NOMINAL FLUX(lm)	11.0429	CIE CLASS	DIRECT	<input type="checkbox"/> UP,DN(C180-360)	0.7,49.5	
LAMPS INSIDE	40	<input type="checkbox"/> up (%)	1.4	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	24	<input type="checkbox"/> down (%)	98.6	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2022-03-21

☐ Range: 0 - 180DEG  
☐ Interval: 2.0DEG  
 Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.450  
 Humidity:65.0%  
 Test Distance:5.749m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:

°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	143.4	143.6	144.0	144.3	144.4	144.3	143.9	143.6	0- 10	13.84	13.84	3.13,3.13
20	136.3	136.6	137.3	138.0	138.4	138.1	137.3	136.6	10- 20	39.87	53.71	12.2,12.2
30	124.8	125.3	126.3	127.3	127.8	127.5	126.3	125.3	20- 30	61.03	114.7	26,26
40	109.2	109.7	111.0	112.4	113.1	112.6	111.1	109.8	30- 40	74.61	189.4	42.9,42.9
50	89.41	90.04	91.68	93.31	94.19	93.75	91.92	90.20	40- 50	78.62	268.0	60.7,60.7
60	66.03	66.71	68.63	70.64	71.47	71.10	69.01	66.89	50- 60	72.09	340.1	77,77
70	39.66	40.36	42.67	44.84	45.62	45.31	43.23	40.84	60- 70	55.41	395.5	89.5,89.5
80	12.35	14.67	17.52	19.27	19.26	19.00	17.99	16.00	70- 80	31.33	426.8	96.6,96.6
90	0.1570	1.003	2.686	3.273	0.1168	2.128	3.112	2.510	80- 90	8.729	435.5	98.6,98.6
100	0.3900	0.3946	0.3947	0.3667	0.2811	0.2904	0.3590	0.3354	90-100	0.8163	436.3	98.8,98.8
110	0.7065	0.6776	0.6581	0.6321	0.5525	0.5307	0.5589	0.5756	100-110	0.4993	436.8	98.9,98.9
120	1.009	0.9464	0.9291	0.9079	0.8285	0.7805	0.8108	0.8276	110-120	0.7354	437.6	99.1,99.1
130	1.271	1.187	1.174	1.165	1.090	1.026	1.037	1.063	120-130	0.8955	438.5	99.3,99.3
140	1.471	1.391	1.369	1.383	1.300	1.235	1.229	1.260	130-140	0.9494	439.4	99.5,99.5
150	1.628	1.565	1.535	1.564	1.471	1.416	1.381	1.439	140-150	0.8875	440.3	99.7,99.7
160	1.763	1.724	1.718	1.712	1.631	1.587	1.574	1.607	150-160	0.7297	441.0	99.8,99.8
170	1.897	1.872	1.887	1.857	1.814	1.782	1.790	1.798	160-170	0.4926	441.5	100,100
180	2.014	2.001	2.028	2.014	2.016	2.001	2.025	2.014	170-180	0.1814	441.7	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 236.71 lm

%lum = 53.6%

%lamp = 53.6%

Conical surface Flux(120deg): 340.06 lm

%lum = 77.0%


%lamp = 77.0%

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:  
Test Date:2022-03-21

□ Range: 0 - 180DEG  
□ Interval: 2.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.450  
Humidity:65.0%  
Test Distance:5.749m [K=1.0000]  
Remarks:

## LUMINANCE LIMITATION CURVES

NAME: 2835 IP20	TYPE: 2835 160LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	225	11218
80	7104	10095
75	11170	12410
70	11585	12481
65	13177	13845
60	13195	13733
55	14006	14438
50	13899	14268
45	14377	14683


C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators:  
Test Date: 2022-03-21

☐ Range: 0 - 180DEG  
☐ Interval: 2.0DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.00.450  
Humidity: 65.0%  
Test Distance: 5.749m [K=1.0000]  
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: 2835 IP20	TYPE: 2835 160LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															
	Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.90	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.79	.74	.81	.76	.72	.77	.74	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.61	.68	.63	.59	.57
4.0	.70	.61	.54	.68	.60	.53	.65	.58	.52	.63	.57	.52	.61	.55	.51	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.45	.54	.49	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.39	.36
7.0	.50	.42	.35	.50	.41	.35	.48	.40	.35	.46	.40	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.29
9.0	.42	.34	.28	.41	.34	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.26
10.0	.39	.31	.26	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:  
Test Date:2022-03-21

□ Range: 0 - 180DEG  
□ Interval: 2.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.450  
Humidity:65.0%  
Test Distance:5.749m [K=1.0000]  
Remarks:

### WEC AND CCEC

NAME: 2835 IP20	TYPE: 2835 160LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Wall Exitance Coefficients(WEC)
0.0						
1.0	.313 .178 .056	.306 .174 .055	.292 .167 .053	.279 .161 .052	.267 .155 .050	
2.0	.294 .161 .049	.288 .158 .049	.275 .153 .048	.264 .148 .046	.253 .143 .045	
3.0	.272 .145 .043	.266 .143 .043	.255 .138 .042	.245 .134 .041	.235 .130 .040	
4.0	.251 .130 .038	.246 .129 .038	.236 .125 .037	.227 .122 .037	.218 .119 .036	
5.0	.232 .118 .034	.227 .117 .034	.218 .114 .033	.210 .111 .033	.203 .108 .033	
6.0	.215 .108 .031	.211 .106 .031	.203 .104 .030	.196 .102 .030	.189 .099 .030	
7.0	.200 .099 .028	.196 .098 .028	.189 .096 .028	.183 .094 .027	.176 .092 .027	
8.0	.187 .091 .026	.183 .090 .026	.177 .088 .025	.171 .087 .025	.165 .085 .025	
9.0	.175 .085 .024	.172 .084 .023	.166 .082 .023	.161 .081 .023	.156 .079 .023	
10.0	.164 .079 .022	.162 .078 .022	.156 .077 .022	.152 .075 .021	.147 .074 .021	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Ceiling Cavity Exitance Coefficients(CCEC)
0.0	.201 .201 .201	.172 .172 .172	.117 .117 .117	.067 .067 .067	.022 .022 .022	
1.0	.191 .167 .145	.164 .143 .125	.112 .099 .086	.064 .057 .050	.021 .018 .016	
2.0	.183 .143 .109	.157 .123 .094	.108 .085 .065	.062 .049 .038	.020 .016 .012	
3.0	.176 .125 .085	.151 .108 .074	.103 .075 .052	.060 .044 .030	.019 .014 .010	
4.0	.168 .112 .069	.144 .097 .060	.099 .067 .042	.057 .039 .025	.018 .013 .008	
5.0	.161 .102 .058	.138 .088 .050	.095 .061 .036	.055 .036 .021	.018 .012 .007	
6.0	.154 .093 .050	.132 .081 .044	.091 .057 .031	.053 .033 .018	.017 .011 .006	
7.0	.147 .086 .044	.126 .075 .038	.087 .053 .027	.051 .031 .016	.016 .010 .005	
8.0	.140 .081 .040	.121 .070 .035	.084 .049 .025	.049 .029 .015	.016 .009 .005	
9.0	.134 .076 .036	.116 .066 .032	.080 .046 .022	.047 .027 .013	.015 .009 .004	
10.0	.129 .071 .033	.111 .062 .029	.077 .044 .021	.045 .026 .012	.015 .008 .004	

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:  
Test Date:2022-03-21

☐ Range: 0 - 180DEG  
☐ Interval: 2.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.450  
Humidity:65.0%  
Test Distance:5.749m [K=1.0000]  
Remarks:

### UGR(Unified Glare Rating) Table

NAME: 2835 IP20					TYPE: 2835 160LED 24V			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.: 0.01*0.5			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	24.7	26.2	25.0	26.4	26.7	24.8	26.3	25.1	26.6	26.8
	3H	26.1	27.5	26.4	27.8	28.0	26.3	27.7	26.7	28.0	28.3
	4H	26.6	28.0	27.0	28.2	28.5	26.9	28.3	27.3	28.5	28.8
	6H	26.9	28.2	27.3	28.5	28.8	27.3	28.6	27.7	28.9	29.2
	8H	26.9	28.1	27.3	28.4	28.7	27.4	28.7	27.8	29.0	29.3
	12H	26.8	28.0	27.2	28.3	28.7	27.5	28.7	27.9	29.0	29.3
4H	2H	25.3	26.6	25.6	26.9	27.2	25.4	26.7	25.7	27.0	27.3
	3H	26.9	28.1	27.3	28.4	28.7	27.1	28.3	27.5	28.6	28.9
	4H	27.5	28.6	27.9	28.9	29.3	27.8	28.9	28.2	29.2	29.6
	6H	27.9	28.8	28.3	29.2	29.6	28.3	29.2	28.7	29.6	30.0
	8H	27.9	28.8	28.3	29.2	29.6	28.5	29.3	28.9	29.7	30.2
	12H	27.9	28.7	28.3	29.1	29.5	28.6	29.4	29.0	29.8	30.2
8H	4H	27.7	28.6	28.2	29.0	29.4	28.0	28.9	28.4	29.3	29.7
	6H	28.2	29.0	28.7	29.4	29.9	28.6	29.3	29.1	29.8	30.2
	8H	28.3	29.0	28.8	29.4	29.9	28.9	29.5	29.3	30.0	30.4
	12H	28.3	28.9	28.8	29.3	29.8	29.0	29.6	29.5	30.1	30.6
12H	4H	27.7	28.6	28.2	29.0	29.4	28.0	28.8	28.4	29.2	29.6
	6H	28.3	28.9	28.8	29.4	29.9	28.6	29.3	29.1	29.7	30.2
	8H	28.4	28.9	28.9	29.4	29.9	28.9	29.5	29.4	29.9	30.4
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H		+ 0.2 / - 0.2					+ 0.1 / - 0.2				
1.5H		+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H		+ 0.2 / - 0.3					+ 0.2 / - 0.3				

CIE Pub.117, 441.7 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.8)  
Area: 0.01 m2

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:  
Test Date:2022-03-21

☐ Range: 0 - 180DEG  
☐ Interval: 2.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.450  
Humidity:65.0%  
Test Distance:5.749m [K=1.0000]  
Remarks:


```

Range: 0 - 180DEG
Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

```

### ISOCANDELA DIAGRAM

NAME: 2835 IP20	TYPE: 2835 160LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:  
Test Date:2022-03-21

☐ Range: 0 - 180DEG  
☐ Interval: 2.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.450  
Humidity:65.0%  
Test Distance:5.749m [K=1.0000]  
Remarks:



### AAI Figure

NAME: 2835 IP20	TYPE: 2835 160LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:  
Test Date:2022-03-21

☐ Range: 0 - 180DEG  
☐ Interval: 2.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.450  
Humidity:65.0%  
Test Distance:5.749m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM

NAME: 2835 IP20	TYPE: 2835 160LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators:  
Test Date: 2022-03-21

☐ Range: 0 - 180DEG  
☐ Interval: 2.0DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.00.450  
Humidity: 65.0%  
Test Distance: 5.749m [K=1.0000]  
Remarks:

## LED Avg.L Report

NAME: 2835 IP20	TYPE: 2835 160LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	13248
L_0~180 (75) av	11300
L_0~180 (85) av	3630
L_90~270 (65) av	13284
L_90~270 (75) av	11520
L_90~270 (85) av	9630
L_45 (65) av	13277
L_45 (75) av	11423
L_45 (85) av	8720

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators:  
 Test Date: 2022-03-21

☐ Range: 0 - 180DEG  
☐ Interval: 2.0DEG  
 Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.00.450  
 Humidity: 65.0%  
 Test Distance: 5.749m [K=1.0000]  
 Remarks:

# Planar Illuminance Curve



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators:  
 Test Date: 2022-03-21

☐ Range: 0 - 180DEG  
☐ Interval: 2.0DEG  
 Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.00.450  
 Humidity: 65.0%  
 Test Distance: 5.749m [K=1.0000]  
 Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 2835 IP20	TYPE: 2835 160LED 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:

Table--1

UNIT: cd

C (DEG) □ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	146	146	146	146	146	146	146	146	146	146	146	146	146	146	146	146			
5	146	146	146	146	146	146	146	146	146	146	146	146	146	146	146	146			
10	143	144	144	144	144	144	144	144	144	144	144	144	144	144	144	143			
15	141	141	141	142	142	142	142	143	142	142	142	142	142	142	141	141			
20	136	137	137	137	137	138	138	138	138	138	138	137	137	137	137	136			
25	132	133	133	133	133	134	134	135	135	134	134	134	133	133	133	132			
30	125	125	125	126	126	127	127	128	128	127	127	127	126	125	125	125			
35	119	119	120	120	121	122	122	122	122	122	122	121	121	120	120	119			
40	109	110	110	111	111	112	112	113	113	113	113	112	111	110	110	109			
45	102	102	102	103	104	105	105	106	106	106	106	105	104	103	102	102			
50	89.4	89.9	90.0	91.1	91.7	93.0	93.3	94.1	94.2	93.8	93.8	92.6	91.9	90.6	90.2	89.5			
55	80.4	80.9	81.1	82.2	82.8	84.2	84.6	85.5	85.5	85.2	85.1	83.9	83.2	81.8	81.3	80.5			
60	66.0	66.4	66.7	67.8	68.6	70.0	70.6	71.4	71.5	71.3	71.1	70.0	69.0	67.6	66.9	66.1			
65	55.7	56.1	56.4	57.6	58.5	60.0	60.6	61.4	61.5	61.3	61.1	60.0	59.0	57.5	56.7	55.8			
70	39.7	40.0	40.4	41.7	42.7	44.2	44.8	45.6	45.6	45.4	45.3	44.2	43.2	41.7	40.8	39.8			
75	28.9	29.3	29.6	31.1	32.1	33.7	34.2	34.9	34.9	34.6	34.6	33.6	32.7	31.2	30.3	29.2			
80	12.3	14.2	14.7	16.3	17.5	19.0	19.3	19.6	19.3	18.9	19.0	18.4	18.0	16.9	16.0	14.7			
85	0.20	6.45	6.90	8.41	9.77	11.1	11.2	11.0	9.17	9.67	10.1	10.1	10.2	9.44	8.64	7.39			
90	0.16	0.77	1.00	1.84	2.69	3.38	3.27	2.55	0.12	1.41	2.13	2.69	3.11	2.98	2.51	1.69			
95	0.23	0.25	0.31	0.49	0.81	1.14	1.06	0.72	0.17	0.25	0.58	0.83	1.09	1.08	0.87	0.43			
100	0.39	0.39	0.39	0.39	0.39	0.42	0.37	0.34	0.28	0.28	0.29	0.34	0.36	0.35	0.34	0.33			
105	0.52	0.50	0.50	0.50	0.49	0.47	0.46	0.44	0.38	0.37	0.38	0.40	0.41	0.42	0.42	0.42			
110	0.71	0.68	0.68	0.67	0.66	0.64	0.63	0.62	0.55	0.52	0.53	0.54	0.56	0.57	0.58	0.58			
115	0.83	0.79	0.78	0.78	0.77	0.76	0.75	0.74	0.67	0.63	0.63	0.65	0.66	0.68	0.68	0.69			
120	1.01	0.95	0.95	0.94	0.93	0.92	0.91	0.91	0.83	0.79	0.78	0.79	0.81	0.82	0.83	0.84			
125	1.12	1.06	1.05	1.04	1.03	1.02	1.01	1.02	0.94	0.89	0.88	0.89	0.91	0.91	0.93	0.94			
130	1.27	1.21	1.19	1.18	1.17	1.17	1.16	1.17	1.09	1.05	1.03	1.02	1.04	1.05	1.06	1.09			
135	1.36	1.30	1.27	1.26	1.26	1.26	1.26	1.27	1.18	1.14	1.11	1.11	1.12	1.14	1.15	1.17			
140	1.47	1.43	1.39	1.37	1.37	1.38	1.38	1.40	1.30	1.26	1.23	1.23	1.23	1.25	1.26	1.30			
145	1.54	1.50	1.46	1.44	1.44	1.46	1.46	1.47	1.37	1.33	1.31	1.31	1.29	1.31	1.33	1.38			
150	1.63	1.60	1.57	1.53	1.54	1.56	1.56	1.57	1.47	1.44	1.42	1.41	1.38	1.40	1.44	1.48			
155	1.69	1.66	1.63	1.60	1.60	1.64	1.63	1.63	1.54	1.50	1.48	1.48	1.45	1.47	1.51	1.54			
160	1.76	1.75	1.72	1.69	1.72	1.72	1.71	1.72	1.63	1.60	1.59	1.59	1.57	1.57	1.61	1.64			
165	1.81	1.80	1.78	1.76	1.80	1.78	1.77	1.77	1.70	1.68	1.66	1.66	1.66	1.64	1.68	1.72			
170	1.90	1.89	1.87	1.86	1.89	1.87	1.86	1.86	1.81	1.79	1.78	1.78	1.79	1.78	1.80	1.84			
175	1.96	1.95	1.94	1.93	1.95	1.93	1.93	1.94	1.89	1.88	1.87	1.87	1.88	1.87	1.89	1.92			
180	2.01	2.00	2.00	2.00	2.03	2.01	2.01	2.02	2.02	2.00	2.00	2.01	2.03	2.01	2.01	2.02			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:  
Test Date:2022-03-21

□ Range: 0 - 180DEG  
□ Interval: 2.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.00.450  
Humidity:65.0%  
Test Distance:5.749m [K=1.0000]  
Remarks: