


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: 2835 256LED 24V 2700K	TYPE: 256D 2835 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 116.53 lm/W
MODEL	2700K 4.8W	I _{max} (cd)	188.4	S/MH(C0/180)	1.27	
NOMINAL POWER(W)	4.8	LOR(%)	100.0	S/MH(C90/270)	1.21	
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	553.98	□ UP,DN(C0-180)	0.8,53.7	
NOMINAL FLUX(lm)	4.32794	CIE CLASS	DIRECT	□ UP,DN(C180-360)	0.7,44.9	
LAMPS INSIDE	128	□ up (%)	1.4	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	24	□ down (%)	98.6	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-08-24

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

°	C0	C45	C90	C135	C180	C225	C270	C315	°	zone	total	%lum, lamp
10	184.9	186.7	187.4	186.4	184.5	182.7	181.9	182.9	0- 10	17.78	17.78	3.21,3.21
20	175.9	179.5	180.8	178.9	175.0	171.5	170.0	172.0	10- 20	51.04	68.82	12.4,12.4
30	161.2	166.4	168.3	165.5	159.8	154.5	152.3	155.2	20- 30	77.73	146.5	26.5,26.5
40	141.1	147.8	150.3	146.6	139.2	132.2	129.3	133.2	30- 40	94.36	240.9	43.5,43.5
50	116.0	124.3	127.3	122.9	113.6	105.0	101.4	106.2	40- 50	98.58	339.5	61.3,61.3
60	86.53	96.41	99.99	94.72	83.71	73.58	69.43	74.96	50- 60	89.51	429.0	77.4,77.4
70	53.94	64.99	69.05	63.13	50.76	39.74	35.35	41.21	60- 70	68.02	497.0	89.7,89.7
80	21.60	31.89	35.99	30.17	18.29	9.960	6.720	11.07	70- 80	38.03	535.0	96.6,96.6
90	0.2059	5.578	7.614	5.165	0.1834	0.3114	0.3399	0.5604	80- 90	11.02	546.1	98.6,98.6
100	0.4613	0.3663	0.3423	0.3827	0.4192	0.5092	0.5518	0.4997	90-100	0.9942	547.1	98.8,98.8
110	0.8349	0.6868	0.6461	0.7178	0.7571	0.8302	0.8679	0.8113	100-110	0.6312	547.7	98.9,98.9
120	1.223	1.055	1.012	1.084	1.116	1.151	1.196	1.147	110-120	0.9327	548.6	99,99
130	1.577	1.398	1.357	1.427	1.445	1.456	1.462	1.437	120-130	1.147	549.8	99.2,99.2
140	1.854	1.707	1.649	1.740	1.716	1.712	1.688	1.693	130-140	1.224	551.0	99.5,99.5
150	2.080	1.973	1.915	2.002	1.935	1.936	1.883	1.910	140-150	1.153	552.1	99.7,99.7
160	2.263	2.194	2.203	2.214	2.137	2.135	2.125	2.129	150-160	0.9530	553.1	99.8,99.8
170	2.444	2.416	2.438	2.418	2.366	2.361	2.384	2.374	160-170	0.6439	553.7	100,100
180	2.608	2.604	2.643	2.628	2.606	2.601	2.641	2.628	170-180	0.2368	554.0	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 300.39 lm

%lum = 54.2%

%lamp = 54.2%

Conical surface Flux(130deg): 473.06 lm

%lum = 85.4%


%lamp = 85.4%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-24

° Range: 0 - 180DEG
 ° Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity:65.0%
 Test Distance:5.749m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

NAME: 2835 256LED 24V 2700K	TYPE: 256D 2835 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	25158	53508
80	24864	41478
75	31460	43235
70	31519	40399
65	34858	41666
60	34589	40019
55	36471	40794
50	36053	39643
45	37188	40096


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2021-08-24

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: 2835 256LED 24V 2700K	TYPE: 256D 2835 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															
	Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.03	.99	.95	1.01	.97	.94	.97	.93	.90	.92	.90	.87	.89	.86	.84	.82
2.0	.90	.83	.77	.88	.82	.76	.84	.79	.74	.81	.76	.72	.77	.74	.71	.68
3.0	.79	.71	.64	.77	.70	.63	.74	.68	.62	.71	.66	.61	.68	.64	.60	.57
4.0	.70	.61	.54	.68	.60	.54	.66	.59	.53	.63	.57	.52	.61	.56	.51	.49
5.0	.62	.53	.47	.61	.53	.46	.59	.51	.46	.57	.50	.45	.55	.49	.44	.42
6.0	.56	.47	.41	.55	.47	.40	.53	.45	.40	.51	.45	.39	.50	.44	.39	.37
7.0	.51	.42	.36	.50	.42	.36	.48	.41	.35	.47	.40	.35	.45	.39	.34	.32
8.0	.46	.38	.32	.46	.37	.32	.44	.37	.31	.43	.36	.31	.41	.35	.31	.29
9.0	.42	.34	.29	.42	.34	.28	.41	.33	.28	.39	.33	.28	.38	.32	.28	.26
10.0	.39	.31	.26	.39	.31	.26	.37	.30	.26	.36	.30	.25	.35	.30	.25	.23



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-08-24

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: 2835 256LED 24V 2700K	TYPE: 256D 2835 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Wall Exitance Coefficients(WEC)
0.0						
1.0	.311 .177 .056	.304 .173 .055	.289 .166 .053	.276 .159 .051	.265 .153 .049	
2.0	.292 .160 .049	.286 .157 .048	.273 .152 .047	.262 .147 .046	.251 .142 .045	
3.0	.270 .144 .043	.265 .142 .043	.254 .137 .042	.243 .133 .041	.234 .129 .040	
4.0	.250 .130 .038	.244 .128 .038	.234 .124 .037	.225 .121 .037	.217 .118 .036	
5.0	.231 .118 .034	.226 .116 .034	.217 .113 .033	.209 .110 .033	.201 .108 .032	
6.0	.214 .107 .031	.210 .106 .030	.202 .103 .030	.195 .101 .030	.188 .099 .029	
7.0	.199 .098 .028	.195 .097 .028	.188 .095 .027	.182 .093 .027	.176 .091 .027	
8.0	.186 .091 .026	.183 .090 .025	.176 .088 .025	.170 .086 .025	.165 .085 .025	
9.0	.174 .084 .024	.171 .083 .023	.165 .082 .023	.160 .080 .023	.155 .079 .023	
10.0	.164 .078 .022	.161 .078 .022	.156 .076 .022	.151 .075 .021	.146 .074 .021	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Ceiling Cavity Exitance Coefficients(CCEC)
0.0	.201 .201 .201	.172 .172 .172	.117 .117 .117	.067 .067 .067	.022 .022 .022	
1.0	.191 .167 .145	.164 .143 .125	.112 .099 .086	.064 .057 .050	.021 .018 .016	
2.0	.183 .143 .109	.157 .123 .094	.108 .085 .066	.062 .050 .039	.020 .016 .013	
3.0	.176 .125 .085	.151 .108 .074	.103 .075 .052	.060 .044 .031	.019 .014 .010	
4.0	.168 .112 .069	.144 .097 .060	.099 .068 .042	.057 .040 .025	.018 .013 .008	
5.0	.161 .102 .058	.138 .088 .051	.095 .062 .036	.055 .036 .021	.018 .012 .007	
6.0	.154 .093 .050	.132 .081 .044	.091 .057 .031	.053 .033 .018	.017 .011 .006	
7.0	.147 .087 .044	.126 .075 .039	.087 .053 .027	.051 .031 .016	.016 .010 .005	
8.0	.140 .081 .040	.121 .070 .035	.084 .049 .025	.049 .029 .015	.016 .010 .005	
9.0	.134 .076 .036	.116 .066 .032	.080 .046 .023	.047 .027 .013	.015 .009 .004	
10.0	.129 .072 .034	.111 .062 .029	.077 .044 .021	.045 .026 .012	.015 .008 .004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-08-24

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: 2835 256LED 24V 2700K					TYPE: 256D 2835 24V					WEIGHT:				
SPEC.:					DIM.:					SERIAL No.:				
MFR.:					SUR.: 0.01*0.5					Shielding Angle:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3				
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3				
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2				
Room dimensions					Viewed crosswise					Viewed endwise				
x = 2H y = 2H					27.6	29.1	27.9	29.4	29.6	28.2	29.7	28.4	29.9	30.1
3H					29.2	30.6	29.5	30.8	31.1	30.0	31.4	30.3	31.6	31.9
4H					29.8	31.1	30.1	31.4	31.7	30.8	32.1	31.1	32.4	32.7
6H					30.2	31.4	30.6	31.7	32.1	31.5	32.7	31.9	33.0	33.4
8H					30.3	31.5	30.7	31.8	32.1	31.8	33.0	32.1	33.3	33.6
12H					30.4	31.5	30.7	31.8	32.2	32.0	33.2	32.4	33.5	33.8
4H 2H					28.4	29.7	28.7	30.0	30.3	28.8	30.1	29.1	30.4	30.7
3H					30.2	31.3	30.5	31.6	32.0	30.8	32.0	31.2	32.3	32.6
4H					30.9	32.0	31.3	32.3	32.7	31.8	32.9	32.2	33.2	33.6
6H					31.5	32.4	31.9	32.8	33.2	32.6	33.6	33.1	34.0	34.4
8H					31.6	32.5	32.1	32.9	33.3	33.0	33.9	33.4	34.3	34.7
12H					31.7	32.5	32.2	32.9	33.4	33.3	34.1	33.8	34.5	35.0
8H 4H					31.3	32.2	31.8	32.6	33.0	32.1	33.0	32.5	33.4	33.8
6H					32.1	32.8	32.5	33.2	33.7	33.1	33.9	33.6	34.3	34.7
8H					32.3	33.0	32.8	33.4	33.9	33.6	34.3	34.1	34.7	35.2
12H					32.5	33.1	33.0	33.5	34.1	34.1	34.6	34.6	35.1	35.6
12H 4H					31.4	32.2	31.8	32.6	33.0	32.1	32.9	32.6	33.3	33.8
6H					32.2	32.8	32.7	33.3	33.8	33.2	33.9	33.7	34.3	34.8
8H					32.5	33.1	33.0	33.6	34.1	33.7	34.3	34.2	34.8	35.3
Variations with the observer position at spacings(CIE Pub.117):														
S = 1.0H					+ 0.1 / - 0.2					+ 0.1 / - 0.2				
1.5H					+ 0.2 / - 0.4					+ 0.2 / - 0.3				
2.0H					+ 0.2 / - 0.4					+ 0.1 / - 0.3				

CIE Pub.117, 554.0 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.1)
Area: 0.005 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-08-24

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

NAME: 2835 256LED 24V 2700K	TYPE: 256D 2835 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	57	45	38	56	45	38	55	44	38	31
0.80	67	55	48	66	55	48	64	54	47	40
1.00	75	64	57	74	63	56	72	65	56	49
1.25	82	72	65	81	71	64	78	69	63	56
1.50	87	77	70	86	76	70	82	75	69	61
2.00	94	86	79	92	84	78	89	82	77	69
2.50	98	90	84	96	89	83	92	86	81	73
3.00	102	95	89	99	93	88	95	90	86	77
4.00	106	100	95	103	98	94	99	94	91	82
5.00	108	103	99	106	101	97	101	97	94	85
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2021-08-24

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: 2835 256LED 24V 2700K	TYPE: 256D 2835 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-08-24

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks:

AAI Figure

NAME: 2835 256LED 24V 2700K	TYPE: 256D 2835 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-08-24

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity:65.0%
 Test Distance:5.749m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

NAME: 2835 256LED 24V 2700K	TYPE: 256D 2835 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2021-08-24

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
 Humidity: 65.0%
 Test Distance: 5.749m [K=1.0000]
 Remarks:

LED Avg.L Report

NAME: 2835 256LED 24V 2700K	TYPE: 256D 2835 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	32655
L_0~180 (75) av	27674
L_0~180 (85) av	16312
L_90~270 (65) av	32489
L_90~270 (75) av	27785
L_90~270 (85) av	24286
L_45 (65) av	32566
L_45 (75) av	27679
L_45 (85) av	21429

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2021-08-24

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2021-08-24

☐ Range: 0 - 180DEG
☐ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity: 65.0%
Test Distance: 5.749m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 2835 256LED 24V 2700K	TYPE: 256D 2835 24V	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.01*0.5	Shielding Angle:

Table--1

UNIT: cd

C (DEG) □ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	188	188	188	188	188	188	188	188	188	188	188	188	188	188	188	188			
5	187	188	188	188	188	188	188	188	187	187	187	186	186	186	187	187			
10	185	186	187	187	187	187	186	186	184	183	183	182	182	182	183	184			
15	182	184	185	185	185	185	184	183	181	180	179	178	178	178	179	181			
20	176	178	179	181	181	180	179	177	175	173	172	170	170	170	172	174			
25	171	173	175	176	176	176	174	172	170	167	165	164	164	164	166	168			
30	161	164	166	168	168	168	166	163	160	157	155	153	152	153	155	158			
35	154	157	160	161	162	161	159	156	152	149	146	144	144	144	147	150			
40	141	145	148	150	150	150	147	143	139	135	132	130	129	130	133	137			
45	132	136	139	141	142	141	138	134	130	125	122	119	119	119	123	127			
50	116	121	124	127	127	126	123	119	114	109	105	102	101	102	106	111			
55	105	110	114	117	117	116	112	108	102	96.7	92.9	89.6	89.0	90.2	94.1	98.9			
60	86.5	92.4	96.4	99.6	100.0	98.9	94.7	89.7	83.7	77.8	73.6	70.1	69.4	70.7	75.0	80.2			
65	73.7	79.9	84.2	87.6	88.0	86.8	82.4	77.1	70.8	64.7	60.2	56.6	55.9	57.2	61.6	67.2			
70	53.9	60.3	65.0	68.5	69.1	67.6	63.1	57.4	50.8	44.4	39.7	36.1	35.3	36.7	41.2	46.9			
75	40.7	47.0	51.7	55.3	55.9	54.5	49.9	44.0	37.4	31.1	26.6	23.0	22.4	23.6	28.0	33.7			
80	21.6	27.5	31.9	35.4	36.0	34.6	30.2	24.7	18.3	13.6	9.96	7.26	6.72	7.75	11.1	15.6			
85	11.0	15.8	19.6	22.8	23.3	22.1	18.2	13.9	8.00	5.26	3.21	1.69	1.39	2.08	3.90	6.65			
90	0.21	3.29	5.58	7.33	7.61	7.01	5.17	2.94	0.18	0.35	0.31	0.30	0.34	0.40	0.56	0.74			
95	0.27	0.59	1.38	1.74	1.68	1.66	1.19	0.52	0.25	0.29	0.34	0.37	0.39	0.38	0.36	0.30			
100	0.46	0.39	0.37	0.35	0.34	0.36	0.38	0.44	0.42	0.46	0.51	0.54	0.55	0.53	0.50	0.45			
105	0.60	0.52	0.48	0.45	0.45	0.46	0.50	0.57	0.55	0.59	0.63	0.67	0.68	0.67	0.62	0.57			
110	0.83	0.74	0.69	0.66	0.65	0.66	0.72	0.78	0.76	0.78	0.83	0.86	0.87	0.87	0.81	0.75			
115	0.99	0.89	0.83	0.80	0.79	0.81	0.86	0.93	0.90	0.92	0.96	0.99	1.01	1.00	0.95	0.89			
120	1.22	1.11	1.06	1.01	1.01	1.03	1.08	1.15	1.12	1.12	1.15	1.18	1.20	1.18	1.15	1.09			
125	1.37	1.25	1.19	1.16	1.15	1.17	1.22	1.31	1.25	1.26	1.27	1.30	1.31	1.30	1.26	1.23			
130	1.58	1.47	1.40	1.36	1.36	1.38	1.43	1.51	1.44	1.45	1.46	1.46	1.46	1.46	1.44	1.41			
135	1.69	1.60	1.52	1.49	1.48	1.51	1.56	1.64	1.56	1.57	1.56	1.56	1.56	1.56	1.54	1.53			
140	1.85	1.77	1.71	1.66	1.65	1.69	1.74	1.81	1.72	1.72	1.71	1.71	1.69	1.70	1.69	1.70			
145	1.95	1.88	1.81	1.77	1.76	1.81	1.86	1.91	1.81	1.80	1.80	1.80	1.76	1.79	1.78	1.79			
150	2.08	2.03	1.97	1.92	1.92	1.98	2.00	2.05	1.93	1.94	1.94	1.93	1.88	1.90	1.91	1.93			
155	2.15	2.11	2.06	2.02	2.03	2.08	2.09	2.13	2.02	2.02	2.01	2.02	1.97	1.98	2.00	2.02			
160	2.26	2.23	2.19	2.16	2.20	2.21	2.21	2.24	2.14	2.14	2.14	2.14	2.13	2.10	2.13	2.15			
165	2.33	2.32	2.28	2.25	2.30	2.29	2.29	2.32	2.23	2.23	2.22	2.23	2.24	2.19	2.22	2.25			
170	2.44	2.43	2.42	2.39	2.44	2.42	2.42	2.44	2.37	2.36	2.36	2.37	2.38	2.35	2.37	2.39			
175	2.52	2.52	2.51	2.50	2.53	2.52	2.51	2.53	2.46	2.46	2.47	2.47	2.49	2.46	2.48	2.50			
180	2.61	2.60	2.60	2.61	2.64	2.62	2.63	2.63	2.61	2.61	2.60	2.61	2.64	2.62	2.63	2.63			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2021-08-24

□ Range: 0 - 180DEG
□ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.450
Humidity:65.0%
Test Distance:5.749m [K=1.0000]
Remarks: